

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2905585](#)

For any questions, you can email us directly:

sales@integrated-circuit.com




Extract from the online catalog

ST-OV4- 24DC/ 24DC/4-PRO

Order No.: 2905585

The illustration shows the version ST-OV4- 24DC/24DC/1-PRO



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2905585>

Pluggable protection circuit power optocoupler, with signal logic, pluggable on 4-position basic termination blocks, input: 24 V DC, output: short-circuit resistant, 18-36 V DC/4 A

Commercial data	
GTIN (EAN)	 4 017918 107611
sales group	G101
Pack	10 pcs.
Customs tariff	85364190
Catalog page information	Page 139 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
10/17/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Input data	
Nominal input voltage U_N	24 V DC \pm 50%
Switching threshold "0" signal, voltage	5 V DC
Switching threshold "1" signal voltage	8.5 V DC
Typical input current at U_N	6.5 mA

ST-OV4- 24DC/ 24DC/4-PRO Order No.: 2905585

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2905585>

Typical response time	300 µs
Typical turn-off time	700 µs
Status display	Yellow LED
Operating voltage display	Yellow LED
Type of protection	Protection against polarity reversal
Protective circuit/component	Polarity protection diode
Transmission frequency	100 Hz

Output data

Output nominal voltage range	18 V DC ... 36 V DC
Limiting continuous current	4 A (see derating curve)
Min. load current	1 mA
Current limitation at short-circuits	Approx. 70 A
Voltage drop at max. limiting continuous current	200 mV
Output circuit	3-conductor, ground-referenced
Indication	Red LED
Type of protection	Protection against polarity reversal
	Free-wheeling diode
Protective circuit/component	Damping diode
Output nominal voltage range	5 V DC ... 36 V DC
Limiting continuous current	50 mA
Voltage drop at max. limiting continuous current	≤ 1.5 V
Output circuit	2-wire, floating
Type of protection	Protection against polarity reversal
Protective circuit/component	Polarity protection diode

General data

Width	27 mm
Height	63.5 mm
Depth	114 mm
Test voltage input/output	2.5 kV AC
Test voltage output/output	2.5 kV AC
Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	0 °C ... 70 °C
Mounting position	Any
Assembly instructions	In rows with zero spacing

ST-OV4- 24DC/ 24DC/4-PRO Order No.: 2905585
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2905585>

Standards/regulations	IEC 60664
	EN 50178
	IEC 62103
Rated surge voltage / insulation	Basic insulation

Certificates / Approvals





Certification

GOST



Diagrams/Drawings

Diagram




ST-OV4- 24DC/ 24DC/4-PRO Order No.: 2905585

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2905585>



Circuit diagram



1 = protection and signal logic

ST-OV4- 24DC/ 24DC/4-PRO Order No.: 2905585

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2905585>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;