

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Macraigor Systems LLC](#)
[U2D-MIPS](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

usb²Demon™



The usb²Demon is a BDM/JTAG interface used in the design, debug, and programming of microprocessor and microcontroller based embedded systems. One side of the usb²Demon interfaces to a USB 1.1 or USB 2.0 port of a host PC and the other side connects to an OCD (On-Chip Debug) port on the target system. As with all Macraigor interface devices, the usb²Demon can simultaneously debug up to 255 devices on a single scan chain. In addition, up to 16 usb²Demons can be connected to a single host machine.

The usb²Demon is designed to be a major upgrade from the Wiggler series of OCD connections and, for many targets, is also significantly faster than a Raven. It supports configurable JTAG/BDM clock rates up to 20 MHz.

The usb²Demon is compatible with Windows and Linux hosts. Supported versions of Linux are Red Hat 7.2 – 9 and Fedora Core 2.

List Price: \$750

Macraigor
Macraigor
Macraigor
Macraigor
Macraigor Systems
Complete JTAG Debug Support

Supported Debuggers and Tools

The usb²Demon is fully compatible with all of Macraigor's software tools, including our free OCD Commander debugger, free GNU toolkit distributions, OCD Flash Programmer application, and our production line test tools.

In addition, several commercial third-party debuggers can interface to the usb²Demon. A partial list of our debugger partners includes:

- Accelerated Technology/ Mentor Graphics
- Allant (ARM)
- Arc (Metaware)
- Altium
- DDC-I
- Green Hills Software
- IAR Systems
- Metrowerks
- Microcross
- Microsoft
- Paradigm Systems
- Red Hat
- Viosoft

For a complete list of compatible debuggers, please visit our web site.

Theory of Operation

The usb²Demon operates as a converter between the target JTAG/BDM signals and host debugging commands. Power is supplied by the USB interface so that no external supply is necessary. The buffers that interface to the target OCD signals are powered by the target itself, allowing the usb²Demon to automatically match target voltages between 5.0 V and 2.2 V.

Supported Processors

AMCC:	PPC405, PPC440
AMD:	SC520, Athlon, Duron, AU1000, AU1100, AU15x0
ARM:	7TDMI, 710T, 720T, 740T, 9TDMI, 920T, 922T, 940T, 946T, 1136J-S
Broadcom:	BCM1250, BCM7115
Freescale:	MC9328MX1, 56300, 56600, 56800, StarCore, 683xx, MPC603e, MPC8xx, MPC5xx, MPC5554, MPC740, MPC745, MPC750, MPC755, MPC8240, MPC8245, MPC8247/8248, MPC8250, MPC8255, MPC8260, MPC8264/65/66, MPC8270/71/72, MPC8280, MPC8540, MPC8560, MPC8541, MPC8555
IBM:	PPC603e, PPC740, PPC750
IDT:	RC323xx
Intel XScale® Technology:	PXA21x, PXA25x, PXA26x, PXA27x, IOP3xx, IXC1100, IXP42x, IXP46x, IXP24xx, IXP28xx, 80200, 80219, 8032x, 8033x
MIPS:	4Kc/p/m/e, 5Kc
NEC:	VR5432, VR5500
Net Silicon:	NetARM+10, NetARM+40, NetARM+50, NS7520, NS9750
PLX:	IOP480
Phillips:	PR1900
Toshiba:	TX49
Transmeta:	Efficeon
Triscend:	E5, A7

For a more complete and up to date list of supported processors, please visit our web site.

Macraigor Systems LLC

www.macraigor.com • Sales Inquiries: 206-855-9269

Macraigor Systems is a leading supplier of BDM/JTAG connection solutions for on-chip debugging of 32 and 64-bit embedded microprocessors. Macraigor Systems' solutions are designed for price-sensitive customers. These solutions include a suite of software tools that supports Windows 9x, NT, ME, XP, Linux and Solaris host systems. Macraigor Systems supports all major embedded microprocessor architectures, including AMD, ARM, ColdFire, CPU32 Series, PowerPC, MIPS and the XScale microarchitecture.