

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1607748](#)

For any questions, you can email us directly:

sales@integrated-circuit.com




Extract from the online catalog

VC-AMS 5

Order No.: 1607748

The illustration shows the product version VC-AMS 4



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1607748>

Contact insert module, for panel mounting frames, with screw connection, 5-pos. + PE, 690 V / 70 A

Commercial data

GTIN (EAN)	 4 017918 969202
sales group	D238
Pack	5 pcs.
Customs tariff	85366990
Catalog page information	Page 353 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
03/27/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Note	Plug connectors may only be connected/disconnected when under no load.
Connection method	Screw connection
	Screw connection
Tightening torque	1.2 Nm ... 1.8 Nm

VC-AMS 5 Order No.: 1607748

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1607748>

Ambient temperature (operation)	-40 °C ... 100 °C
Pollution degree	3
Surge voltage category	III
Number of positions	5
Insertion/withdrawal cycles	≥ 500
Design	VC3
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	6
Connection in acc. with standard	IEC / EN
Conductor cross-section	0.5 mm² ... 16 mm²
Connection cross-section AWG	20 ... 5
Stripping length of the individual wire	12 mm

Material data

Inflammability class acc. to UL 94	V0
Contact material	CuZn
Contact surface material	hard-silver plated
Contact carrier material	PA

Electrical characteristics

Rated voltage (III/3)	690 V
Rated surge voltage	6 kV
	6 kV
Rated current	70 A
	70 A

Certificates / Approvals

Certification CUL, UL

Accessories

Item	Designation	Description
Plug/Adapter		
1600027	CP-HCC 4	Coding profile, Color: red

VC-AMS 5 Order No.: 1607748

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1607748>

Diagrams/Drawings

Dimensioned drawing

VC-AMS 5 Order No.: 1607748

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1607748>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;