

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[5603253](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog

UM-DELTA V/D/SI/BFI


Order No.: 5603253



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5603253>

VARIOFACE interface module with fuse and fuse failure display

Commercial data

GTIN (EAN)	 4 017918 923082
Note	Made-to-order
sales group	I630
Pack	1 pcs.
Customs tariff	85369010

<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal voltage U_N	24 V DC
Max. current carrying capacity per branch	50 mA (in as-supplied state, with one 50 mAF fuse, max. 1 A permitted)
Number of positions	16
Width	61 mm
Height	126 mm
Depth	71 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any

UM-DELTA V/D/SI/BFI Order No.: 5603253

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5603253>

Standards/regulations	IEC 60664
	IEC 60664 A
	DIN VDE 0110
	DIN VDE 0160 (in parts)

Connection data

Connection 1	PCB connection
Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	7 mm
Connection 2	Flat-ribbon cable connection
Type of connection	Pluggable

Certificates / Approvals



Certification

CUL, UL

UM-DELTA V/D/SI/BFI Order No.: 5603253

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5603253>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;