

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Hammond Manufacturing](#)
[DTSF3150](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Air Conditioner Accessories

Neoprene Gasket Kit

- Replacement for standard supplied gasket.
- Self-adhesive cellular neoprene gasket.
- Supplied in 10 foot rolls, 0.19"x0.75".
- For side mount units greater than 3500 BTU/H, two gasket kits are required.

Part No.	1481DJ10
----------	-----------------

Replacement Grill

- Replacement grill for air conditioners.
- Packaged individually.

Black Part No.	RAL 7032 Beige Part No.	Use with Air Conditioner
PG3BK	PG3RAL	DTS1200 - DTS3500
PG5BK	PG5RAL	DTS8000 - DTS12000
n/a	AFF1	DTT4500

Replacement Filters

- Packaged in quantities of 5.
- Made of synthetic fibers.
- Re-usable up to 20 times.
- 100% resistant to humidity.
- Filters have a mass filtering level of 67%.

Part No.	Dimensions		Use With Air Conditioner	Filter Density (g/m ²)
	A	B		
DTSF3150	inch 8.30 mm 210	inch 8.30 mm 210	DTS1200 - DTS6000	150
DTSF5150	inch 11.00 mm 280	inch 11.00 mm 280	DTS8000 - DTS12000	150
DTTF5150	inch 11.81 mm 300	inch 11.81 mm 300	DTT4500	150

Remote Door Switch

- Permits convenient door activated on-off function of air conditioners. Mounts to flange of any Hammond enclosure.
- Can be wired normally open or normally closed.
- 115/230 V AC

Part No.	FLKDS
----------	--------------



Lifting Lugs

- Packaged in quantities of 2.
- Used for lifting, transporting and installation of air conditioners.
- 8 mm diameter.
- For use with DTS3500 - DTS12000 and DTT4500.

Part No.	LL8
----------	------------

Climate Control

Water Condensate Evaporator



Part No.	KVDTX
----------	--------------

- High performance evaporation kit
- Easy to retrofit on any cooling unit

Technical Data	
Max. Water Volume	13.5 oz (400 ml)
Evaporation Rate	3.4 oz/hr (100 ml/hr)
Electrical Data	
Voltage(s)	230v /115v
Frequency	50/60 Hz
Voltage Range	100-240v
Max. Power	125 W
Power Range	20-110 W
Nominal Current	0.5 A (230v) / 0.8 A (115v)
Starting Current	1.3 A
Zero Water Current	0.09 A (230v) / 0.18 A (115v)
Mechanical Data	
Height x Width x Depth	3.35" x 10.35" x 4.00" (85 x 263 x 102 mm)
Finish	Stainless Steel
Weight	2.6 lbs (1.175 Kg)

Technical references and DXF downloads available at www.hammfg.com

All dimensions in inches unless specified otherwise