



Distributor of ITT Cannon, LLC: Excellent Integrated System Limited
Datasheet of DAM-15S-F179A - D-Sub Connector Receptacle, Female Sockets 15 Position
Through Hole Wire Wrap

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ITT Cannon, LLC](#)
[DAM-15S-F179A](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Datasheet for part number DAM15SF179A

Our Catalog Part Number: DAM-15S-F179A
Our Global Manufacturing Part Number: 053512-0968
Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*M

Product Datasheet	
General	D*M High reliable D-Sub Connectors
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	200
Contact Arrangement	15 contacts size 20
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	7.5 A max
Contact Resistance	7.5 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	tin
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Socket
Contact Type	Wire wrap
Contact Material	copper alloy
Contact Finish	gold over nickel
Hardware	.120" (3,05mm) Through Hole