



**Distributor of ITT Cannon, LLC: Excellent Integrated System Limited**  
Datasheet of DEM-9P-L-NMBK52 - D-Sub Connector Plug, Male Pins 9 Position Panel Mount,  
Through Hole, Right Angle Solder

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ITT Cannon, LLC](#)  
[DEM-9P-L-NMBK52](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Datasheet for part number DEM9PLNMBK52

|   |
|---|
| Our Catalog Part Number: DEM-9P-L-NMBK52                              |
| Our Global Manufacturing Part Number: 053516-1454                     |
| Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*M |

| Product Datasheet               |   |
|---------------------------------|---|
| General                         | D*M High reliable D-Sub Connectors          |
| Wire Gauge Range AWG            | AWG 20-28                                   |
| Mating Cycles                   | 200   |
| Contact Arrangement             | 9 contacts size 20                          |
| Dielectric Withstanding Voltage | 1000 VAC at sea level                       |
| Current Rating                  | 7.5 A max                                   |
| Contact Resistance              | 7.5 milli Ohm max                           |
| Operating Temperature           | -55°/+125°                                  |
| Salt Spray Test                 | 20 hours                                    |
| Shell Material                  | steel                                       |
| Shell Finish                    | 50 microinch gold over 100 microinch copper |
| Insulator Material              | Thermoplastic, type PCT UL 94V-0            |
| Insulator Color                 | black                                       |
| Gender                          | Pin   |
| Contact Type                    | Right angled PCB                            |
| Contact Material                | copper alloy                                |
| Contact Finish                  | 50 microinch gold over 100 microinch copper |
| Hardware                        | .120" (3,05mm) Through Hole                 |