

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Recom Power](#)
[RAC03-12SA](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Features

Regulated Converters

- Ultracompact AC-DC Power Supply
- 3 Watt PCB Mount Package
- Universal Input Voltage Range
- Low Cost Pinless Design
- Very Low No Load Input Current
- Short Circuit Protected
- +85°C Maximum Operating Temperature
- Efficiency to 77%

Description

The RAC03 series is an ultra-compact low cost universal input AC/DC power module for PCB mounting via slots in the PCB (pinless connectors). It features ultralow no-load power consumption, short circuit, overload and output overvoltage protection as well as a built-in EMC Class B filter.

Selection Guide

Part Number	Input Range (VAC)	Output Voltage (VDC)	Output Current (mA)	Efficiency (%)	Max Capacitive Load
RAC03-3.3SA	90-264	3.3	900	70	14000µF
RAC03-05SA	90-264	5	600	72	8000µF
RAC03-09SA	90-264	9	333	76	3200µF
RAC03-12SA	90-264	12	250	76	1500µF
RAC03-15SA	90-264	15	200	76	1000µF
RAC03-24SA	90-264	24	125	77	470µF

Specifications (typical at 25°C and after warm up time unless otherwise specified)

Input Voltage Range	90-264VAC or 120-370VDC	
Rated Power	3 Watts max	
Input Frequency Range (for AC Input)	47-63Hz	
Input Current (full load)	115/230VAC	75/55mA max.
No Load Power Consumption	115/230VAC	120/180mW typ.
Inrush Current (<0.5ms)	115/230VAC	20/50A max.
Leakage Current	0.3mA max	
Output Voltage Accuracy (full load)	single outputs	±10%
Line Voltage Regulation (low line, high line at full load)	3.3V output	±5% typ
	All others	±2% typ
Load Voltage Regulation (0% to 100% full load)	3.3V output	±5% typ
	All others	±2% typ
Output Ripple and Noise (20MHz limited)	100mVp-p max	
Operating Frequency	132kHz typ	
Hold-up time	15ms min.	
Minimum Load	0%	
RMS Isolation Voltage (input to output)	3.75kVAC / 1 minute	
Temperature Coefficient	±0.02%/°C typ	
Isolation Resistance	100 MΩ max	
Short Circuit Protection	Hiccup, Automatic Restart	
Output Overvoltage Protection	Zener Clamping Diode	
Operating Temperature Range (natural convection)	no derating	-0°C to +60°C
	with derating	-40°C to +85°C
Storage Temperature Range	-55°C to +125°C	
Humidity	95% RH max	
Case Material	Epoxy with Fibreglass (UL94V-0)	
	Fully potted	
Package Weight	26g	
Packing Quantity	12 pcs	
EMC	Conducted and Radiated	EN 55022 Class B
	Noise Immunity	EN 55024
MTBF (+25°C)	using MIL-HDBK-217F	> 250 x 10 ³ hours

POWERLINE

AC/DC-Converter

with 3 year Warranty




3 Watt Single Output



RAC03-A

Derating Graph (Ambient Temperature)





Please Read Application Notes

POWERLINE


AC/DC-Converter

RAC03-SA Series

Typical Characteristics



Standard Package Style and Pinning



RAC03-A

Standard Application Circuit

Compact single output regulated power supply

Suggested fuse rating:

1A Slow Blow

