

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[Ametherm](#)  
[AS35 2R035](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



# DATA SHEET

## Part Number: AS35 2R035



### Electrical Specifications:

Resistance @ 25°C	2.0 Ω ± 25 %
Max Steady State Current Up to 65°C	35.0 A
Max recommended energy rating (Joules)	700.00 J
Actual failure point of instantaneous energy (Joules)	1400.00 J
Resistance @ 100% of Max Current	0.012 Ω
Resistance @ 50% of Max Current	0.027 Ω
Body Temperature @ 100% Current rating	220 °C
Dissipation Constant	78.20 mW/°C
Thermal Time Constant	55 seconds
Material Type	B
ROHS Compliant	Yes
MSL (moisture sensitivity level)	# 2

### Mechanical Specifications:

D	36.0 mm Max
T	8.5 mm Max
S	19.0mm Nom
Straight Leads Coating run down	6.5 mm Max
L	22.0 mm Nom
A (Lead Width)	2.2 mm Nom
B	5.5 mm Nom
C (Lead Thickness)	0.8 mm Nom

Revision Date: 5/14/09

**Ametherm, Inc.** 3111 N. Deer Run Road #4 Carson City, NV 89701  
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670  
[www.ametherm.com](http://www.ametherm.com)