

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[Ametherm](#)
[AS35 20010](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



DATA SHEET

Part Number: AS35 20010



Electrical Specifications:

Resistance @ 25°C	20.0 Ω ± 25 %
Max Steady State Current Up to 65°C	10.0 A
Max recommended energy rating (Joules)	500.00 J
Actual failure point of instantaneous energy (Joules)	1000.00 J
Resistance @ 100% of Max Current	0.150 Ω
Resistance @ 50% of Max Current	0.380 Ω
Body Temperature @ 100% Current rating	210 °C
Dissipation Constant	78.20 mW/°C
Thermal Time Constant	55 seconds
Material Type	G
ROHS Compliant	Yes
MSL (moisture sensitivity level)	# 2

Mechanical Specifications:

D	36.0 mm Max
T	9.0 mm Max
S	19.0mm Nom
Straight Leads Coating run down	6.0 mm Max
L	22.0 mm Nom
A (Lead Width)	2.2 mm Nom
B	5.5 mm Nom
C (Lead Thickness)	0.8 mm Nom

Revision Date: 4/10/09

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670
www.ametherm.com