

Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Samtec, Inc.](#)

[MODS-F-8P8C-L-S-1-1-TH](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



MODS-F SERIES

SINGLE RIGHT ANGLE MOD JACK WITH LED

SPECIFICATIONS



For complete specifications and recommended PCB layouts see www.samtec.com?MODS-F

- Insulator Material:** Nylon 46 (For both -SM and -TH)
- Contact Material:** Phosphor Bronze
- Shield Material:** Copper Alloy
- Plating:** Gold on Contacts, Nickel on Shield, Gold on Tails
- Operating Temp Range:** -25°C to +90°C
- Current Rating:** 1.5 A per contact
- Voltage Rating:** 120 VAC max
- Contact Resistance:** 20 mΩ max
- Minimum Cycles:** 500
- System Applications:** CAT3
- Packaging:** Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.
- RoHS Compliant:** Yes
- Lead-Free Solderable:** -TH=Yes (Wave Solder only) -SM=Yes



APPLICATION SPECIFIC OPTION

Other plating options available. Call Samtec.



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM