

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[3056132](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



Extract from the online
catalog

RWO 8

Order No.: 3056132



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3056132>

Feed-through terminal block, Connection method: Bolt connection,
Load current : 125 A, Cross-section: 2.5 mm² - 35 mm², AWG 14 - 2,
Connection direction of the conductor to plug-in direction: 0 °,
Width: 20.3 mm, Color: gray

Commercial data

GTIN (EAN)	
Note	Made-to-order
sales group	A420
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 60 (NTK-2010)

Product notes

WEEE/RoHS-compliant since:
06/24/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Number of levels	1
Number of connections	2
Color	gray

RWO 8 Order No.: 3056132

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3056132>

Insulating material	PA
Inflammability class acc. to UL 94	V0

Dimensions

Width	20.3 mm
-------	---------

Technical data

Maximum load current	125 A
Rated surge voltage	6 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I_N	125 A
Nominal voltage U_N	1000 V

Connection data

Conductor cross section solid min.	2.5 mm ²
Conductor cross section solid max.	35 mm ²
Conductor cross section stranded min.	2.5 mm ²
Conductor cross section stranded max.	35 mm ²
Conductor cross section AWG/kcmil min.	14
Conductor cross section AWG/kcmil max	2
Connection method	Bolt connection
Screw thread	M8
Tightening torque, min	4.5 Nm
Tightening torque max	5 Nm

Accessories

Item	Designation	Description
General		
3075171	RW 8-F	Flange cover, Color: gray
0820222	ZB 16,3:UNPRINTED	Terminal marking
0820248	ZB 20,3:UNPRINTED	Terminal marking

RWO 8 Order No.: 3056132

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3056132>

Marking


0828295	TMT (EX9,5)R	Terminal marking with 9.5 mm strip height, continuous, without color print, for all terminals with ZB or ZBF groove, can be labeled using a thermal transfer printer, 1 roll = 50 m
---------	--------------	---

Tools

1205079	SZS 1,0X6,5 VDE	Screwdriver, bladed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip
---------	-----------------	--

Diagrams/Drawings

Dimensioned drawing



RWO 8 Order No.: 3056132

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3056132>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;