

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[2278377](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## MCO 1,5/ 4-G1R-3,5 KMGY


Order No.: 2278377

The illustration shows the 5-pos. version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2278377>

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: light gray, Assembly: Soldering, Article with lateral pin exit

Commercial data	
GTIN (EAN)	 4 046356 292986
sales group	F057
Pack	50 pcs.
Customs tariff	85366990
Catalog page information	Page 181 (CC-2009)

### Product notes

WEEE/RoHS-compliant since:  
05/09/2007



<http://www.download.phoenixcontact.com>  
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Dimensions / positions

Pitch	3.5 mm
Dimension a	10.5 mm
Number of positions	4
Pin dimensions	0,8 x 0,8 mm

MCO 1,5/ 4-G1R-3,5 KMGY Order No.: 2278377

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2278377>

Hole diameter	1.2 mm
<b>Technical data</b>	
Range of articles	MCO 1,5/..-G1R
Insulating material group	I
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/2)	160 V
Rated voltage (II/2)	320 V
Nominal current I <sub>N</sub>	8 A
Nominal voltage U <sub>N</sub>	160 V
Maximum load current	8 A
Insulating material	PA
Inflammability class acc. to UL 94	V0
Nominal voltage, UL/CUL Use Group B	300 V
Nominal current, UL/CUL Use Group B	8 A
Nominal voltage, UL/CUL Use Group D	300 V
Nominal current, UL/CUL Use Group D	8 A

**Certificates / Approvals**



Certification CUL, UL

**Accessories**


Item	Designation	Description
<b>General</b>		
2199618	CR MSTBO-G1	Coding section

MCO 1,5/ 4-G1R-3,5 KMGY Order No.: 2278377


<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2278377>

**Diagrams/Drawings**

Drilling plan/solder pad geometry



Diagram



Derating curve for: MC 1,5/...-ST-3,5 with MCO 1,5/...-G1L(R)-3,5 KMGY

MCO 1,5/ 4-G1R-3,5 KMGY Order No.: 2278377  
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2278377>

---

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;