

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[3M](#)

[3M5557NP-2MMSQ-100](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

3M

Water Contact Indicator Tape

5557NP

Technical Data

March, 2006

Product Description

3M™ Water Contact Indicator Tape 5557NP quickly shows indication when contacted by water. When water comes in contact with the tape surface, it rapidly **changes from white to red**. The tape is designed to withstand heat and humidity aging without giving false indication. It will continue to show indication even after prolonged submersion in water. The adhesive is a high performance acrylic protected by a silicone coated film release liner.

Product Construction

Backing	Adhesive	Release Liner	Color
Paper	Acrylic	Polyester Film	White

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Stainless Steel: (90° Peel Adhesion, 72 hr. Dwell)	82 oz./in. width (88 N/100 mm)	D-3330
Adhesion to Polycarbonate: (90° Peel Adhesion, 72 hr. Dwell)	47 oz./in. width (52 N/100 mm)	D-3330
Tape Thickness:	8.6 mils (0.218 mm)	D-3652
Release Liner Thickness:	2.0 mils (0.051 mm)	D-3652
Humidity Resistance:*	55°C, 95% R.H.	



0 hrs. exposure



7 days

Arrow identifies the location of 1 drop of water applied for 1 minute after the specified aging cycle. Test circles are 1/2" diameter.

*Tape is applied to polycarbonate panel and hung vertically in heat/humidity chamber.

3M™ Water Contact Indicator Tape

5557NP

- General Information**
- Tape may be die cut using rotary die cutting process.
 - Substrate should be smooth, clean, dry and oil-free to insure good wet-out and adequate adhesion.
 - Adhesive should not be applied at temperatures <50°F (10°C) (best if room temperature or higher).
 - Not useful for indicating contact with other non-aqueous liquids such as oils and organic solvents.
 - Standard roll size = 12" x 180 yards (304.8 mm x 165 m).

- Application Ideas**
- As a water contact indicator in handheld or portable electronic devices such as cell phones, PDA's, pagers, MP3 players, game players, CD players, cordless phones, two-way radios, laptops, digital or film cameras, video cameras, etc.
 - As a water contact indicator for other products with sensitivity to aqueous liquids.

Key Attributes	Features	Benefits
	Paper backing	Highly absorbent, quickly transports water to show indication. Does not falsely indicate water contact in high humidity exposures. Performance not degraded by past high humidity exposures. Rotary die cuttable. Can readily form variety of labels.
	Acrylic adhesive	Excellent UV, chemical and temperature resistance. Very high bond strength to most surfaces including low surface energy plastics such as polypropylene and powder coatings.
	Polyester film liner	Excellent die cuttability.

Shelf Life To obtain best performance, use this product within 12 months from date of manufacture and store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

3M™ Water Contact Indicator Tape

5557NP

Technical Information and Data

The technical information and data, recommendations, and other statements provided in this document are based on tests or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed.

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-251-8634. Address correspondence to: 3M Electronics Markets Materials Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244 or 1-877-369-2923. In Canada, phone: 1-800-634-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M Electronics

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
1-800-251-8634 phone
651-778-4244 fax
www.3M.com/electronics



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2006 60-5002-0103-7 (3/06)