



Distributor of ASSMANN WSW Components: Excellent Integrated System Limited
Datasheet of AU-Y1007-3-R - Connector Receptacle USB TypeB 3.0, Super Speed 9 Position
Through Hole, Right Angle, Horizontal

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:







[ASSMANN WSW Components](#)
[AU-Y1007-3-R](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

A
B
C
D
E
F
G
H
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

1	2	3	4	5	6	7
---	---	---	---	---	---	---

RoHS compliant



- NOTES:**
- Material:
 - 1.1 Housing: PBT+30%GF UL94V-0, Color Blue
 - 1.2 Shell: Brass
 - 1.3 Contact :Copper Alloy
 - FINISH:
 - 2.1 Contact Area: Selective 15u"Au
Solder Area:Tin Plated
Under: Ni Plated
 - MECHANICAL:
 - 3.1 Mating Force:3.57kgf Max.
 - 3.2 Unmating Force:1.02kgf Min
 - 3.3 Durability:1500 cycles Min
 - ELECTRICAL:
 - 4.1 Current Rating:1.0A
 - 4.2 Dielectric Strength:100V AC FOR 1 MINUTE
 - 4.3 Contact Resistance:30mΩ Max
 - 4.4 Insulation Resistance:100 MΩ Min
 5. Operating temperature: -55°C TO +85°C
 - 6.PACKING: Tray

Scale	Free					
TOLERANCE						
.X	±0.30					
.XX	±0.20					
.XXX	±0.10					
DIM	TOL					
X.°	±5°					
Angle	TOL					
UNIT	mm					

Id.					
Drawn					
Modification					
Date	07.06.2013				
Name	Winnie				

Customer-No.	ASSMANN WSW-No.	ASSMANN WSW components
	AU-Y1007-3-R	
	ASS 5779 CO	rev00
Replace		SHEET