

Excellent Integrated System Limited




Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[E-Switch](#)
[P227EE1CXC](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



CIRCUIT: DPST
 CONTACT CONFIGURATION



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT MATERIAL: COPPER ALLOY W/ SILVER PLATE
5. RATING: 7A@125V, 4A@250
6. CONTACT RESISTANCE: 20MΩ MAX @ 5V DC 1A
7. DIELECTRIC STRENGTH: AC 1500V RMS
8. OPERATING FORCE: 550±150gf TYP.
9. TRAVEL: FULL:5.5, LOCK:4.0

REV.	ECN No.	DESCRIPTION	DATE	CHKD
D	15234	UPDATED DESCRIPTION	9/2/05	PH
C	11768	REVISED DIMENSION	5/29/02	CB
B	11768	REVISED, AND REDRAWN	10/23/01	CJC
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED		SCALE	DATE	DR	DWG	REV
		1.5:1	10/23/01	CJC	P030113	D
TITLE		P227 EE 1CX C				
		E-SWITCH®				