Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Wurth Electronics Inc 744760247A


For any questions, you can email us directly: sales@integrated-circuit.com




Datasheet of 744760247A - FIXED IND 470NH 500MA 950 MOHM


more than you expect

A Dimensions: [mm]



B Recommended land pattern: [mm]







Properties	Test conditions		Value	Unit	Tol.
Inductance	25.2 MHz	L	0.47	μН	±5%
Q-factor	100 MHz	Q	45		min.
DC Resistance	@ 20°C	R _{DC}	0.95	Ω	max.
Rated current	$\Delta T = 15 \text{ K}$	I _R	500	mA	max.
Self resonant frequency		fres	375	MHz	min.

Scale - 15:1

E General information:

It is recommended that the temperature of the part does not exceed 85°C under worst case operating conditions.

- Ambient temperature: -40°C to +70°C (refering to IR)
 Operating temperature: -40°C to +85°C

- •Storage temperature (on tape & reel): -10°C to +40°C; 30 to 70% RH max. •Test conditions of Electrical Properties: 20°C, 33% RH if not specified differently

DESCRIPTION Projection $\bigoplus \bigoplus$ **WE-RFI Ferrite SMD Inductor** Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (10) 79 42 945 - 0 www.we-online.com eiSos@we-online.com COMPLIANT ROHS&REACH WÜRTH ELEKTRONIK Order - No SIZE 2014-04-10 SSt HBH 744760247A 2007-01-17 SKle 2.0 Size: 0805A CHECKED

extractionic equipment only. This product is not authorized for use in equipment where a higher selects shard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use, retrieved for use in areas such as military, aerospace, avidion, nuclear control, shimarine, transportation (authornofive control, than control, this control, than control, than control, disportation signal, disaster prevention, medical, public information network etc. Wirth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the performance.




Datasheet of 744760247A - FIXED IND 470NH 500MA 950 MOHM

more than you expect


WÜRTH ELEKTRONIK

W** close to center


G Packaging Specification - Tape and Reel [mm]:



		A0	В0	w	P1	т	T1	T2	D0	E1	E2	F	P0	P2	Tape	Packaging Unit
	tolerance	typ.	typ.	+0,3 -0,1	± 0,1	± 0,1	max.	typ.	+0,1 -0,0	± 0,1	min.	± 0,05	± 0,1	± 0,05		
	0603	1,40	1,90	8,00	4,00	0,20	0,10	1,15	1,50	1,75	6,25	3,50	4,00	2,00	Polystyrene	3000
a .	0805A	1,42	2,26	8,00	4,00	0,20	0,10	1,30	1,50	1,75	6,25	3,50	4,00	2,00	Polystyrene	2000
Size	0805C	1,42	2,26	8,00	4,00	0,20	0,10	1,30	1,50	1,75	6,25	3,50	4,00	2,00	Polystyrene	3000
"	1008	2,23	2,73	8,00	4,00	0,20	0,10	1,80	1,50	1,75	6,25	3,50	4,00	2,00	Polystyrene	2000
	1210	2,69	3,56	8,00	4,00	0,20	0,10	2,40	1,50	1,75	6,25	3,50	4,00	2,00	Polystyrene	2000



| Description |



This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such usage.

Notewore Wifth Electronic eitses GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, avaiation, nuclear control, shimarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Wifth Electronic eitses GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.




Datasheet of 744760247A - FIXED IND 470NH 500MA 950 MOHM

more than you expect

H Soldering Specifications:

WÜRTH ELEKTRONIK

H1: Classification Reflow Profile for SMT components:



H2: Classification Reflow Profiles

Profile Feature	Pb-Free Assembly
Preheat - Temperature Min (T _{smin}) - Temperature Max (T _{smax}) - Time (t _s) from (T _{smin} to T _{smax})	150°C 200°C 60-120 seconds
Ramp-up rate (T _L to T _P)	3°C/ second max.
Liquidous temperature (T_L) Time (t_L) maintained above T_L	217°C 60-150 seconds
Peak package body temperature (T _p)	See Table H3
Time within 5°C of actual peak temperature (tp)	20-30 seconds
Ramp-down rate (T _P to T _L)	6°C/ second max.
Time 25°C to peak temperature	8 minutes max.

refer to IPC/JEDEC J-STD-020D

H3: Package Classification Reflow Temperature

	Package Thickness	Volume mm³ <350	Volume mm ³ 350 - 2000	Volume mm³ >2000
PB-Free Assembly	< 1.6 mm	260°C	260°C	260°C
PB-Free Assembly	1.6 - 2.5 mm	260°C	250°C	245°C
PB-Free Assembly	≥ 2.5 mm	250°C	245°C	245°C

refer to IPC/JEDEC J-STD-020D

				Projection ————————————————————————————————————		DESCRIPTION WE-RFI Ferrite	SMD Inductor				
				Würth Elektronik eiSos Gmbl- EMC & Inductive Solutions Max-Eyth-Str. 1	H & Co. KG						
3.0	2014-04-10	SSt	НВН	74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0		Order No.	COMPLIANT ROHS&REACH	SIZE			
2.0	2007-01-17	SKle	-	www.we-online.com eiSos@we-online.com		744760247A	WORTH ELEKTRONIK	A4			
REV	DATE	BY	CHECKED	elous@we-online.com		Size: 0805A					

Insistenctions component has been onesigned and developed for usage in general execution couplinant for the product is a reasonation year, personal injury or death, unless the parties have executed an agreement speciation and reasonation year, and the product is reasonation year, personation in the product is not authorized for the intensity of each unless the parties have executed an agreement speciation to clause severe personal injury or each unless the parties have executed an agreement speciation and unless that it is not authorized to control, transportation signal, disaster prevention, medical, public information network etc.. With Elektronix eSiss GribH & Cox KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.



Datasheet of 744760247A - FIXED IND 470NH 500MA 950 MOHM

more than you expect

I Cautions and Warnings:

The following conditions apply to all goods within the product series of WE-RFI of Würth Elektronik eiSos GmbH & Co. KG:

General

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The usage and operation of the product within ambient conditions, which probably alloy or harm the wire isolation, has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. The product is exposed to the pressure of the potting material with the effect that the core, wire and termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endangered to be affected. After the potting material is cured, the core, wire and termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.

Cleaning agents that are used to clean the customer application might damage or change the characteristics of the component, body, pins or termination

Direct mechanical impact to the product shall be prevented as the core material could flake or in the worst case it could break.

Product specific:

Follow all instructions mentioned in the data sheet, especially:

- The soldering profile has to be complied with according to the technical reflow soldering specification, otherwise this will void the
 warranty.
- •All products shall be used before the end of the period of 12 months based on the product date code, if not a 100% solderability can't be ensured.
- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.

The general and product specific cautions comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable; however, no responsibility is assumed for inaccuracies or incompleteness.

				Projection	DESCRIPTION		
					WE-RFI Ferrite SMD In	nductor	
				Würth Elektronik eiSos GmbH 8 EMC & Inductive Solutions	o. KG		
				Max-Eyth-Str. 1 74638 Waldenburg Germany	Order No.	COMPLIANT	SIZE
3.0	2014-04-10	SSt	HBH	Tel. +49 (0) 79 42 945 - 0	7447000474	ROHS&REACH	
2.0	2007-01-17	SKle	-	www.we-online.com eiSos@we-online.com	744760247A)	A4
REV	DATE	BY	CHECKED	CIOONSWC GRIIITE.COTT	Size: 0805A		

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover With Elektronic Resides Genified & Co Kit or products are neither designed and control, transportation signal, designed personal reliability transportation in signal, designed personal reliability transportation signal, designed personal reliab





Datasheet of 744760247A - FIXED IND 470NH 500MA 950 MOHM

more than you expect

J Important Notes:

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications
It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty,

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve spe cific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further gueries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected



6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights
All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

				Projection		DESCRIPTION		
						WE-RFI Ferrite	SMD Inductor	
				Würth Elektronik eiSos GmbH & EMC & Inductive Solutions	Co. KG			
				Max-Eyth-Str. 1 74638 Waldenburg		Order No.	COMPLIANT	SIZE
3.0	2014-04-10	SSt	HBH	Germany Tel. +49 (0) 79 42 945 - 0		-44-0004-4	ROHS&REACH WÜRTH ELEKTRONIK	
2.0	2007-01-17	SKle	-	www.we-online.com eiSos@we-online.com		744760247A	TO THE REAL PROPERTY.	A4
REV	DATE	BY	CHECKED	CISUS@WE-UTILITE.CUTT		Size: 0805A		

ment has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially equived or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

roll is 65cs RiPH & Co. KG products are neither designed nor intended for use in a nease such as military, acrespace, eviation, nuclear control, submarine, transportation injuried, place to the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Addition, affective fields by evaluation devices for setely must be performed on every electronic component which is useful electrical circulars better quive injuried. and reliability functions or performance.

Addition, affective fields by evaluation devices for setely must be performed on every electronic component which is useful electrical circulars better quive injuried.

Addition, affective fields by evaluation devices for setely must be performed on every electronic component which is useful electrical circulars better quive injuried.

Addition, affective fields by evaluation devices for setely must be performed on every electronic component which is useful electrical circulars better quive injuried.

Addition, affective fields by evaluation devices for every every expected to cause severe personal injury or death, unless the performance of the product is reasonable to expect a failure of the product is reasonable to expect a failure of the product is reasonable to every expected to cause severe personal injury or death, unless the performance of the product is reasonable to expect a failure of the product is reasonable to expect a failure of the product is reasonable to expect a failure of the product is reasonable to expect a failure of the product is reasonable to expect a f