

Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Lumex, Inc.](#)
[OED-LDC15001EB](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

UNCONTROLLED DOCUMENT



PART NUMBER		REV.
OED-LDC15001EB		A
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE

ELECTRO-OPTICAL CHARACTERISTICS (T_c=25°C), P_o=5mW

PARAMETER	SYMBOL	MIN	TYP	MAX	TEST COND	UNITS
PEAK WAVELENGTH	λ	1520	1550	1580	CW	nm
SPECTRAL WIDTH	$\Delta\lambda$	2	5		CW	nm
FORWARD VOLTAGE	V _f		1.2	1.5	CW	V
THRESHOLD CURRENT	I _{th}		8	20		mA
PD MONITOR CURRENT	P _m	100		600	CW	μA
PD DARK CURRENT	I _(DARK)			0.1	V _{R(PD)} =5V	μA
PD CAPACITANCE	C _t	6	15		R _(PD) =5V, f=1MHz	pF
RISE TIME	T _r		0.5		CW, I _{bias} =I _{th}	ns
FALL TIME	T _f		0.5		10-90%	ns
SLOPE EFFICIENCY		0.12	0.15			mW/mA
BEAM DIVERGENCE:	θ		20		CW,	deg.
	θ_L		40		FWHM	deg.

ABSOLUTE MAXIMUM RATINGS (T_c=25°C)

PARAMETER	SYMBOL	MAX	UNITS
OPTICAL POWER	P _o	5(CW)	mW
LD REVERSE VOLTAGE	V _{R(LD)}	2	V
PD REVERSE VOLTAGE	V _{R(PD)}	10	V
PD FORWARD CURRENT	I _{F(PD)}	1.0	mA
OPERATING TEMP.	T _{op}	40 TO + 85	°C
STORAGE TEMP.	T _{stg}	40 TO + 85	°C

WARNING
INVISIBLE LASER RADIATION,
AVOID DIRECT EXPOSURE TO BEAM.

CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±0.25mm (±0.010")

REV. A	PART NUMBER OED-LDC15001EB	<p>CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.</p> <p>RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.</p>	<p>LUMEX INCORPORATED</p> <p>290 E. HELLEN ROAD PALATINE, ILLINOIS 60067 PHONE: 1-847-359-2790 WEB: HTTP://WWW.LUMEX.COM</p>
1550nm LASER DIODE, TO-18 (ø5.6mm) PACKAGE, 5mW OUTPUT.		<p>DRAWN BY: DU</p> <p>CHECKED BY:</p> <p>APPROVED BY:</p> <p>DATE: 5-18-99</p> <p>PAGE: 1 OF 1</p> <p>SCALE: N/A</p>	