

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[US-Lasers, Inc.](#)
[D6355I](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

US-Lasers: 635nm-5mW - Red Laser Diode

[Back to Laser Diodes](#)

VISIBLE LASER DIODE DATA SHEET
ABSOLUTE MAXIMUM RATINGS - (Tc=25 °C)

TECHNICAL DATA for LASER DIODE <ul style="list-style-type: none"> Index Guided MQW Structure Wavelength: 635nm (Typ.) Optical Power: 5mW CW Threshold Current: 40mA (Typ.) Standard Package: 5.6mm 		
Visible laser diode light output	635nm	Pin Out Diagram - Style A
Optical power output	5mW CW	
Package Type	5.6mm	
Built-in photo diode for monitoring laser output		

Items	Symbols	Values	Unit
Optical output power	Po	5	mW
Laser diode reverse voltage	VLDR	2	V
Photo diode reverse voltage	VPDR	30	V
Operating temperature	Topr	-10 ~ +40	°C
Storage temperature	Tstg	-40 ~ +85	°C

OPTICAL and ELECTRICAL CHARACTERISTICS - (Tc=25 °C)							
Items	Symbols	Min.	Typ.	Max.	Unit	Test Condition	
Optical output power	Po	-	5	-	mW	-	
Threshold current	Ith	30	40	60	mA	-	
Operating current	Iop	40	50	70	mA	Po=5mW	
Operating voltage	Vop	2.0	2.4	2.7	V	Po=5mW	
Lasing wavelength	8 D	630	635	645	nm	Po=5mW	
Beam divergence	θ F	8	10	11	deg	Po=5mW	
Beam divergence	θ z	25	31	40	deg	Po=5mW	
Slope Efficiency (mW/mA)	0	0.4	0.5	0.7	-	-	
Monitor current	Im	10	50	90	μ A	Po=5mW, Vr=5V	
Astigmatism	As	-	11	-	μ m	Po=5mW	
MTTF			3000-5,000 hrs.			Po=5mW, NA=0.4	
Emitter Distance to Cap Lens	0.3mm						
Emitter Size	1 x 4 Microns						
Structure	Index Guided						