

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

<u>Desco</u> 66201

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>





Conductive Bottom Layer

Disclaimer: All statements, technical data, and recommendations contained herein are based upon tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. The proper and correct applications of products and data is the responsibility of the user. Statements or recommendations not contained herein shall have no force or effect unless embodied in a written agreement signed by authorized offers of Desco Industries, Inc.

RoHS Compliance Statement

Rohs Compliance Statement None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl tehrs (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at Desco.com.

Tolerances

Width ± .250'

Limited Warranty: Desco warrants for one year that Dual Layer Rubber matting products will be free of defects in materials and workmanship. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by <u>Desco Limited Warranty</u>.

Length ± .250" every 1 linear foot of running material.

Description:

Dual Layer mat is a .060" thick, 2-layer, dissipative dual layer rubber material. It is designed to provide a path to ground and eliminate static charge generation when used as a worksurface table mat, shelf liner, and cart liner. The surface resistance (1 x 10E6 < 1 x 10E9 ohms Rtt) of the color top layer meets the ANSI/ESD S20.20 worksurface required limit and the ANSI/ESD S4.1 recommendation for contact with ESD susceptible items. The conductive (<1 x 10E6 ohms Rtt) black bottom layer reduces the resistance to ground (Rtg) from the top of the surface to the groundable point ground and allows the mats to be used with ESD works



DATE:

Septembe

2012

Color Dissipative Top Layer Electrical Properties:

Property Test Method Value FTMS 101C, M 4046 ANSI/ESD S4.1 Charge Decay: <0.01sec. 1 x 10E6 < 1 x 10E9 ohms Rtt Resistance: Rtg Resistance: ANSI/ESD S4.1 1 x 10E6 < 1 x 10E9 ohms

Specifications:

Thickness:	0.060"
Tolerance:	Thickness ± .005"
Colors*:	Light Blue, Grey, Dark Blue

*Color and texture may vary between lots

Grounding: This material must be properly grounded for optimum electrical performance. See Tech Bulletin TB-2000 for mat grounding instructions.

Cleaning: For optimum electrical performance, surface must be cleaned regularly using an ESD mat cleaner. We suggest using our Reztore Surface & Mat Cleaner. Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.

Use With Continuous Monitor: This material may be used with ESD workstation continuous monitors.

Mat Top Kit Item Numbers

Size	Light Blue	Dark Blue	Grey
24" x 36"	<u>66211</u>	<u>66217</u>	<u>66223</u>
24" x 48"	<u>66212</u>	<u>66218</u>	<u>66224</u>
30" x 60"	<u>66213</u>	<u>66219</u>	<u>66225</u>
30" x 72"	<u>66214</u>	<u>66220</u>	<u>66226</u>
36" x 72"	<u>66215</u>	<u>66221</u>	<u>66227</u>

1 Benchmat, size as specified 1 Ground Cord and Push and Clinch Snap

Roll Material Item Numbers

	Size	Light Blue	Dark Blue	Grey
	24" x 50'	<u>66200</u>	<u>66204</u>	<u>66208</u>
	30" x 50'	<u>66201</u>	<u>66205</u>	<u>66209</u>
	36" x 50'	<u>66202</u>	<u>66206</u>	<u>66210</u>
ľ				

Tray Liner Item Number

Size Light Blue Dark Blue Grey 16" x 24" <u>66228</u>

<u>66216</u> <u>66222</u> Tray liner has 1" radius corners and does not include grounding hardware.

Specifications and procedures subject to change without notice.

Dual Layer Rubber Matting

DESCO	DESCO WEST: 3661 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370	DRAWING NUMBER 66200

© 2012 DESCO INDUSTRIES INC.