



P.C.B Layout

MATERIAL:  
 HOUSING:PBT+30%G.F UL 94V-0  
 CONTACT:BRASS T=0.25mm  
 SHELL:SPCC T=0.30mm  
 PLATING:  
 CONTACT: GOLD AND TIN OVER NICKEL PLATING  
 SHELL: NICKEL OVER ALL PLATING  
 SPECIFICATION:  
 CURRENT-MAX[AMPS]1.5A  
 VOLTAGE-MAX[VOLTS]:30V  
 WITHSTANDING VOLTAGE:500V AC  
 CONTACT RESISTANCE[OHMS]:30mΩ MIN  
 INSULATION RESISTANCE[OHMS]:1000MΩ MIN  
 ENVIRONMENTAL:  
 TEMPERATURE RANGE:-40°C TO+105°C

09/14-15	yang		NEW DWG		AO				
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.				
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表			<h2 style="text-align: center;">CnC Tech, LLC</h2> <p style="text-align: center;">TITLE: USB 4P AM SMT 贴片式成品</p>						
X.X	±0.38	X.X°				±3.00°	APPD:	PRODUCT NO: 1001-011-01101	
X.XX	±0.25	X.XX°	±2.00°	CHECK:	DATE	SCALE	UNIT	TYPE	PAGE
X.XXX	±0.10	X.XXX°	±1.00°	DRAW:	2015.09.09	1:1	mm	Z	1 / 1