

Excellent Integrated System Limited

Stocking Distributor



Click to view price, real time Inventory, Delivery & Lifecycle Information:

[CNC Tech](#)
[740-10010-00300](#)


For any questions, you can email us directly:

sales@integrated-circuit.com


UNIT:mm




HDMI 19P/M MOLDING TYPE
 INNER MOLD NO.:HJ-CT-091
 OUTER MOLD NO.:HJ-CT-092/093
 (MOULD NO.)



导体1/0.32BC
 绝缘HDPF ID0.70
 地线1/0.32BC
 导体1/0.32BC
 铝箔25U*25mm
 展翅铝箔0.044*8+11mm
 绝缘P. skin ID0.95
 编织128/0.12ALMG
 外皮PVC 黑色BK-01 007.3




HDMI 19P/M MOLDING TYPE
 INNER MOLD NO.:HJ-CT-091
 OUTER MOLD NO.:HJ-CT-092/093
 (MOULD NO.)



1.ELECTRICAL TEST
 (1).100% open short & miss wire test
 (2).Insulation resistance:DC/300V 5Mohm(Min)
 (3).Contactor resistance:≤3ohm Max
 2.HDTV-DVD TEST:1080P (高清电视测试: 1080P)
 3.RoHS compliant

⑦	OUT JACKET	16g	OUTER MOLD:45P PVC COLOR:BLACK
⑥	IN JACKET	8g	INNER MOID:CLEAR LDPE
⑤	CONN	2	HDMI 19P/M SOLDER STYLE SHORT BODY PIN 3U" SHELL-PLATED GOLD INSULATION BLACK
④	TUBE	2	HEAT SHRINK TUBE CLEAR OD0.8*L=20mm.
③	TUBE	10	HEAT SHRINK TUBE CLEAR OD2.0*L=6mm .
②	TUBE	10	HEAT SHRINK TUBE BLACK OD0.8*L=9mm.
①	CABLE	1	28#1/0.32BC+FPPE ID0.95*1P+D 1/0.32BC+HDPF ID0.6+AL]*4P+(1/0.32BC+HDPF ID0.70)*1P+(1/0.32BC+HDPF ID0.70)*5C+AL+D 1/0.32BC+B 28#/0.12ALMG+PVC BLACK OD7.3MM

<h2 style="text-align: center;">CNC Tech, LLC</h2> <p style="text-align: center;">Industrial Cable and Connector Technology</p>							
				DRAWN BY	Zhongghs	DRAWING NO.	VG/LJQ-094-002
				CHECKED BY		CUSTOMER	CNC
				APPROVAL BY		ITEM NO.	740-10010-00300
DECIDE BY		DATE	2012-02-14				
VERSIONS/EDITEN	A/0	PROJECTION					

A 4 3 2 1