

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Honeywell Sensing and Productivity Solutions
2TP8-7](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



MICRO SWITCH
 FREEPORT ILLINOIS U.S.A.
 A DIVISION OF HONEYWELL
FED. MFG. CODE 81985

**SWITCH- TOGGLE
 FLUSH KEY**

CATALOG LISTING
2TP8 SERIES
CHART 1

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CATALOG LISTING	CIRCUIT WITH BUTTON IN			ELECTRICAL DATA
	LUG SIDE (1-2,4-5)	CENTER (1-2,4-5)	OPPOSITE LUG (2-3,5-6)	
2TP8-1	ON	OFF	ON	L 191 15A 125, 250, 277 VAC 1/2 HP 125 VAC. 1 HP 250, 277 VAC 5A 125 VAC "L"
2TP8-2	OFF	NONE	ON	
2TP8-3	ON	NONE	ON	
2TP8-21	NONE	OFF	ON	L 192 10A 125, 250, 277 VAC 1/4 HP 125 VAC. 1/2 HP 250, 277 VAC 3A 125 VAC "L"
2TP8-4	MOM OFF	NONE	ON	
2TP8-5	MOM ON	OFF	ON	
2TP8-6	MOM ON	NONE	OFF	
2TP8-7	MOM ON	OFF	MOM ON	
2TP8-8	MOM ON	NONE	ON	
2TP8-51	NONE	ON	MOM ON	
2TP8-61	MOM ON	OFF	NONE	

NOTES

1 - THESE SWITCHES WILL WITHSTAND TEMPERATURE OF 160°F

2 - MICRO SWITCH CATALOG LISTING MARKED ON SIDE OF SWITCH APPLIES ONLY TO "ON" AND "MOMENTARY ON" POSITIONS

3 - SCREWS FURNISHED UNASSEMBLED

THIRD ANGLE PROJECTION

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES
 APPLY TO DIMEN UNITS. DIMENSIONS ARE ONLY FOR REFERENCE UNLESS NOTED TOLERANCES ARE:

NO PLACES	±.004	±.005	±.007	±.010
ONE PLACE	±.003	±.004	±.006	±.008
TWO PLACES	±.002	±.003	±.005	±.007
THREE PLACES	±.001	±.002	±.004	±.006
FOUR PLACES	±.0005	±.001	±.002	±.003

DESIGN UNITS: METRIC US CUSTOMARY

RAP MATERIALS - COMMERCIAL STANDARD
 HONEYWELL SWITCHES APPLY

DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATING IS APPLIED

WEIGHT 14 LB EST

CATALOG LISTING 2TP8 SERIES CHART 1
 ISSUE 17
 REVISIONS:
 A 029448
 B 202714
 C 1 3 APR 01
 RASTER
 10-10284-B
 DRAWN
 JUN 27 JAN 81
 CHECKED
 RELEASE NO. PR-4060
 PAGE 1 OF 1
 REPLACES