

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1881558](#)

For any questions, you can email us directly:

sales@integrated-circuit.com




Extract from the online catalog

MCV 0,5/ 2-G-2,5

Order No.: 1881558

The figure shows a 10-position version of the product



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1881558>

Header, Nominal current: 4 A, Nom. voltage: 80 V, Pitch: 2.5 mm,
 Number of positions: 2, Color: green, Assembly: Soldering

Commercial data	
EAN	4017918156794
Pack	50 pcs.
Customs tariff	85366990
Weight/Piece	0.0007 KG
Catalog page information	Page 141 (CC-2009)

Product notes

WEEE/RoHS-compliant since:
 01/01/2003



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions / positions	
Length	8.1 mm
Pitch	2.5 mm
Dimension a	2.5 mm
Number of positions	2
Pin dimensions	0,8 x 0,8 mm

MCV 0,5/ 2-G-2,5 Order No.: 1881558

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1881558>

Hole diameter	1.2 mm
Technical data	
Insulating material group	I
Rated surge voltage (III/3)	1.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/2)	160 V
Rated voltage (II/2)	320 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	4 A
Nominal voltage U_N	80 V
Maximum load current	4 A
Insulating material	PA
Inflammability class acc. to UL 94	V0

Certificates / Approvals



Certification

CB, CUL, GOST, UL, VDE-PZI

CUL

Nominal voltage U_N	125 V
Nominal current I_N	4 A

UL

Nominal voltage U_N	125 V
Nominal current I_N	4 A

Accessories

Item	Designation	Description
0804853	SK 2,54/2,8:FORTL.ZAHLEN	Marker card, printed horizontally, self-adhesive, 10-section marker strip, 14 identical decades marked 1-10, 11-20 etc. up to 91-100, sufficient for 140 terminal blocks

Marking

MCV 0,5/ 2-G-2,5 Order No.: 1881558

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1881558>

Plug/Adapter


1881435	CP-MC 0,5	Keying profile, is inserted into the groove in the header, red insulating material
---------	-----------	--

Additional products


Item	Designation	Description
1881325	FK-MC 0,5/ 2-ST-2,5	Plug component, Nominal current: 4 A, Nom. voltage: 100 V, Pitch: 2.5 mm, Number of positions: 2, Connection type: Spring-cage conn., Color: green

Diagrams/Drawings

Drilling plan/solder pad geometry



Dimensioned drawing



MCV 0,5/ 2-G-2,5 Order No.: 1881558

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1881558>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;