

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[TE Connectivity Raychem Circuit Protection  
TVB200SC](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

**Tyco / Electronics**  
**Raychem Circuit Protection**  
 308 Constitution Drive  
 Menlo Park, CA 94025-1164  
 Phone: 800-227-4856  
 Fax: 800-227-4866


**SiBar™**  
**Thyristor Surge Protectors**

**PRODUCT: TVB200SC**


DOCUMENT: SCD 24272  
 PCN: 860265  
 REV LETTER: C  
 REV DATE: AUGUST 24, 2004  
 PAGE NO.: 1 OF 2

**Specification Status: RELEASED**

**PHYSICAL DESCRIPTION**



**Marking:**



	A		B		C		D**		H		J		K	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
mm:	4.06	4.57	3.30	3.81	1.90	2.41	1.96	2.11	0.051	0.152	0.15	0.30	0.76	1.27
in*:	(0.160)	(0.180)	(0.130)	(0.150)	(0.075)	(0.095)	(0.077)	(0.083)	(0.002)	(0.006)	(0.006)	(0.012)	(0.030)	(0.050)

	P	S	
	REF	MIN	MAX
mm:	0.51	5.21	5.59
in*:	(0.020)	(0.205)	(0.220)

\* Rounded off approximation

\*\* D DIMENSION SHALL BE MEASURED WITHIN DIMENSION P

**Other Physical Characteristics**

- Form Factor: SMB (Surface Mount, JEDEC DO-214AA Package)
- Lead Material: Tin / lead finish
- Encapsulation Material: Epoxy, meets UL94 V-0 requirements
- Solderability: per MIL-STD-750, Method 2026
- Solder Heat Withstand: per MIL-STD-750, Method 2031
- Solvent Resistance: per MIL-STD-750, Method 1022
- Mechanical Shock: per MIL-STD-750, Method 2016
- Vibration: per MIL-STD-750, Method 2056

Tape and Reel packaging per EIA 481-1

- Agency Recognition: UL
- Precedence: This specification takes precedence over documents referenced herein.
- CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

**Materials Information**

ELV Compliant

**Directive 2000/53/EC Compliant**

**Tyco / Electronics**  
**Raychem Circuit Protection**  
 308 Constitution Drive  
 Menlo Park, CA 94025-1164  
 Phone: 800-227-4856  
 Fax: 800-227-4866

**SiBar™**  
**Thyristor Surge Protectors**

**PRODUCT: TVB200SC**

DOCUMENT: SCD 24272  
 PCN: 860265  
 REV LETTER: C  
 REV DATE: AUGUST 24, 2004  
 PAGE NO.: 2 OF 2

**DEVICE RATINGS @ 25° C (Both Polarities)**

Parameter	Symbol	Value	Units
Repetitive Off-State Voltage, Maximum at ID = 5 µA	VDM	200	V
Non-Repetitive Peak Impulse Current	IPP <sub>1</sub>	100	A
Double exponential Waveform (Notes 1 and 2)	IPP <sub>2</sub>	150	A
IEC61000-4-5 (Voc 1.2/50us) 8/20 µs	IPP <sub>3</sub>	200	A
ITU-T K.20/K.21 (Voc 10/700us) 5/310 µs	IPP <sub>4</sub>	500	A
TIA-968 lightning Type A Metallic 10/560 µs	IPP <sub>5</sub>	400	A
TIA-968 lightning Type A Longit. 10/160 µs	IPP <sub>6</sub>	150	A
TIA-968 lightning Type B (Voc 9/720us) 5/320 µs	IPP <sub>7</sub>	150	A
Critical Rate of Rise of On-State Current	di/dt	500	A/µs
Powered Pulse Amplifier, C=30µF, V=600V	di/dt	330	A/µs
Maximum 2x10 µsec waveform, Voc=2.5kV, Isc=500A peak	di/dt	330	A/µs

**DEVICE THERMAL RATINGS**

Storage Temperature Range	TSTG	-55 to 150	°C
Operating Temperature Range	TA	-40 to 125	°C
Blocking or conducting state			
Overload Junction Temperature Maximum; Conducting state only	TJ	+150	°C
Maximum Lead Temperature for Soldering Purpose; for 10 seconds	TL	+260	°C

**ELECTRICAL CHARACTERISTICS Both polarities (T<sub>J</sub> @ 25°C unless otherwise noted)**

Characteristics	Symbol	Min	Typ	Max	Units
Breakover Voltage (+25°C) (dv/dt = 0.4kV/µs, I <sub>SC</sub> =900mA V <sub>DC</sub> =500V (both polarities))	VBO	----	260	320	V
Breakover Voltage Temperature Coefficient	dVBO/dTJ	----	0.1	-----	%/°C
Off-State Current (VD1= 50V)	ID1	----	-----	2.0	µA
(VD2=VDM)	ID2=IDM	----	-----	5.0	µA
On-State Voltage (IT=1A) (PW ≤ 300 µsec, Duty Cycle ≤ 2% (Note 2))	VT	----	-----	4.0	V
Breakover Current	IBO	----	-----	800	mA
Holding Current (Note 2)	IH	150	----	-----	mA
Peak Onstage Surge Current (Measured @ 60Hz, 1 cycle, 600V)	ITSM	60	----	-----	A
Critical Rate of Rise of Off-State Voltage (Linear waveform, V <sub>D</sub> = 0.8 X Rated V <sub>BO</sub> , T <sub>J</sub> = +25°C)	dv/dt	2000	----	-----	V/µs
Capacitance (f=1.0 Mhz, 50Vdc bias, 1Vrms)	C1	----	55	-----	pF
(f=1.0 Mhz, 2Vdc bias, 1Vrms)	C2	----	115	-----	pF

Note 1. Allow cooling before test second polarity

Note 2. Measured under pulse conditions to reduce heating

**VOLTAGE-CURRENT CHARACTERISTIC**

