

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Molex Connector Corporation](#)
[0026603099](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



NO. OF CKT'S.	DIM. A	DIM. B
2	(3.96±.05) / .156±.002	(17.77) / .306
3	(7.92±.081) / .312±.003	(11.73) / .462
4	(11.89±.08) / .468±.003	(15.70) / .618
5	(15.85±.10) / .624±.004	(19.66) / .774
6	(19.81±.10) / .780±.004	(23.62) / .930
7	(23.77±.10) / .936±.004	(27.58) / 1.086
8	(27.74±.13) / 1.092±.005	(31.55) / 1.242
9	(31.70±.13) / 1.248±.005	(35.51) / 1.398
10	(35.66±.13) / 1.404±.005	(39.47) / 1.554
11	(39.62±.15) / 1.560±.006	(43.43) / 1.710
12	(43.59±.15) / 1.716±.006	(47.40) / 1.866
13	(47.55±.15) / 1.872±.006	(51.36) / 2.022
14	(51.51±.18) / 2.028±.007	(55.32) / 2.178
15	(55.47±.18) / 2.184±.007	(59.28) / 2.334
16	(59.44±.18) / 2.340±.007	(63.25) / 2.490
17	(63.40±.20) / 2.496±.008	(67.21) / 2.646
18	(67.36±.20) / 2.652±.008	(71.17) / 2.802

NOTES:

- PRECEDING ENG. NO. IN CHART DESIGNATES STANDARD PRODUCT.
- SOLDERABILITY: WHEN PARTS ARE SOLDERED AT A TEMPERATURE OF 230°C (446°F) FOR 5 SECONDS, EACH SOLDERED SURFACE SHALL BE A MINIMUM OF 95% COVERED WITH A SMOOTH CONTINUOUS ADHERENT COATING. FOR OTHER INFORMATION SEE ES-152.
- PIN PUSH OUT FORCE: PRIOR TO SOLDERING, A 3 POUND MINIMUM FORCE (IN EITHER DIRECTION) SHALL BE REQUIRED TO PUSH THE PIN OUT OF THE HEADER.
- FOR ADDITIONAL INFORMATION AND TESTING PROCEDURES SEE PS-08-50.
- PARTS ARE STACKABLE END TO END ON (3.96)/.156 CENTERS.
- FOR PART WITH PEG SEE DWG. NO. SDA-42472

MATERIAL: HEADER: GLASS FILLED POLYESTER, 94V-0, MOLDED NATURAL (WHITE).
PIN: BRASS

PLATINGS:

(102) ELECTRO TIN .000450/ .000200 OVER .000200/ .000100 COPPER
(567) SELECT GOLD 15 M.I. MIN SELECT TIN/LEAD 100 M.I. MIN OVER NICKEL OVERALL
(569) SELECT GOLD 30 M.I. MIN SELECT TIN/LEAD 100 M.I. MIN OVER NICKEL OVERALL
FOR ADDITIONAL INFORMATION SE SDES-88.

REL 0588/0604 UCR2002-0752 03/11/02 SAMEC		DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES UNLESS SHOWN		REVISE ONLY ON CAD SYSTEM	
REV TO WW SPEC UCR2002-0017 7/25/01 SAMEC		3 PLACE ± 2 PLACE ± 1 PLACE ±		TITLE FLAT HEADER ASS'Y .156 BENT SQ PINS, W/O PEG 41772 SERIES DRAWING	
REL 0574/0587 UCR2001-0262 9-19-00 SAMEC		DRAWING DIMENSIONS MUST REMAIN WITHIN DIMENSIONS		MOLEX INCORPORATED SHEET NO. DATE 15632L-0032 U.S.A. 1 OF 6 09/09/87	
APP'D: LENZ		SCALE: 1:1		PART NO. DRAWING NO. SEE CHART SD A-41772	
LTR.	REVISIONS	LTR.	REVISIONS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX, INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	



Distributor of Molex Connector Corporation: Excellent Integrated System Limited

Datasheet of 0026603099 - KK 156 HDR ASSY RTAN TIN 9POS

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

ENG. NO.	HEADER NO.	PIN NO.	PLATING	DIM. L	DIM. X	DIM. G GOLD	DIM. Y	DIM. Z	DIM. T TIN	DIM. W	NO-OF CKTS	VOID CKTS	PACKAGING
A-41772-0368/0377	41770-0009/0018	2161-16(102)	102	(25.40) 1.000	(14.86) .585	() N/A	(4.95) .195	(3.56) .140	() OVERALL	90°	9-18	9	BULK PER PK-41772-002
A-41772-0378/0394	41770-0002/0018	2161--56(102) *	102	(17.86) .703	(5.94) .234	() N/A	(4.90) .193	(4.45) .175	() OVERALL	90°	2-18		BULK PER PK-41772-001
A-41772-0412/0428	41770-0002/0018	2161-63(102) *	102	(24.38) .960	(15.06) .593	() N/A	(2.71) .107	(4.06) .160	() OVERALL	90°	2-18		BULK PER PK-41772-001
A-41772-0429/0445	41770-0002/0018	2161-67(102) *	102	(18.69) .736	(10.48) .413	() N/A	(2.71) .107	(2.92) .115	() OVERALL	90°	2-18		BULK PER PK-41772-001
A-41772-0446/0462	41770-0002/0018	2161-21(501)	501	(28.57) 1.125	(17.60) .693	() OVERALL	(4.95) .195	(3.99) .157	() N/A	90°	2-18		BULK PER PK-41772-002
A-41772-0531/0547	41770-0002/0018	2161-62(102)	102	(24.89) .980	(14.86) .585	() N/A	(4.95) .195	(3.05) .120	() OVERALL	90°	2-18		BULK PER PK-41772-002

• ON ASSEMBLIES A-41772-0378 / -0445 THE PIN BEND RADIUS IS TO BE .045 R

A-41772-0368/0377			A-41772-0378/0394			A-41772-0412/0428			A-41772-0429/0445			A-41772-0446/0462			A-41772-0531/0547		
EDP NO.	ENG. NO.	NO OF CKTS	EDP NO.	ENG. NO.	NO OF CKTS	EDP NO.	ENG. NO.	NO OF CKTS	EDP NO.	ENG. NO.	NO OF CKTS	EDP NO.	ENG. NO.	NO OF CKTS	EDP NO.	ENG. NO.	NO OF CKTS
2	26-60-3029		A-41772-0378	2	27-60-3020	A-41772-0412	2		A-41772-0429	2	27-60-3022	A-41772-0446	2	41772-0531	A-41772-0531	2	
3	26-60-3039		A-41772-0379	3		A-41772-0413	3		A-41772-0430	3	27-60-3032	A-41772-0447	3	41772-0532	A-41772-0532	3	
4	26-60-3049		A-41772-0380	4		A-41772-0414	4		A-41772-0431	4	27-60-3042	A-41772-0448	4	41772-0533	A-41772-0533	4	
5	26-60-3059		A-41772-0381	5		A-41772-0415	5		A-41772-0432	5	27-60-3052	A-41772-0449	5	41772-0534	A-41772-0534	5	
6	26-60-3069		A-41772-0382	6		A-41772-0416	6	27-60-3061	A-41772-0433	6	27-60-3062	A-41772-0450	6	41772-0535	A-41772-0535	6	
7	26-60-3079		A-41772-0383	7	27-60-3070	A-41772-0417	7	27-60-3071	A-41772-0434	7	27-60-3072	A-41772-0451	7	41772-0536	A-41772-0536	7	
8	26-60-3089		A-41772-0384	8		A-41772-0418	8		A-41772-0435	8	27-60-3082	A-41772-0452	8	41772-0537	A-41772-0537	8	
9	26-60-3099		A-41772-0385	9		A-41772-0419	9		A-41772-0436	9	27-60-3092	A-41772-0453	9	41772-0538	A-41772-0538	9	
10	26-60-3109		A-41772-0386	10		A-41772-0420	10		A-41772-0437	10	27-60-3102	A-41772-0454	10	41772-0539	A-41772-0539	10	
11	26-60-3119		A-41772-0387	11		A-41772-0421	11		A-41772-0438	11	27-60-3112	A-41772-0455	11	41772-0540	A-41772-0540	11	
12	26-60-3129		A-41772-0388	12		A-41772-0422	12		A-41772-0439	12	27-60-3122	A-41772-0456	12	41772-0541	A-41772-0541	12	
13	26-60-3139		A-41772-0389	13		A-41772-0423	13		A-41772-0440	13	27-60-3132	A-41772-0457	13	41772-0542	A-41772-0542	13	
14	26-60-3149		A-41772-0390	14		A-41772-0424	14		A-41772-0441	14	27-60-3142	A-41772-0458	14	41772-0543	A-41772-0543	14	
15	26-60-3159		A-41772-0391	15		A-41772-0425	15		A-41772-0442	15	27-60-3152	A-41772-0459	15	41772-0544	A-41772-0544	15	
16	26-60-3169		A-41772-0392	16		A-41772-0426	16		A-41772-0443	16	27-60-3162	A-41772-0460	16	41772-0545	A-41772-0545	16	
17	26-60-3179		A-41772-0393	17		A-41772-0427	17		A-41772-0444	17	27-60-3172	A-41772-0461	17	41772-0546	A-41772-0546	17	
18	26-60-3189		A-41772-0394	18		A-41772-0428	18		A-41772-0445	18	27-60-3182	A-41772-0462	18	41772-0547	A-41772-0547	18	

H	SEE SHEET 1	D	SEE SHEET 1	DIMENSIONS SHOWN METRIC INCH UNLESS OTHERWISE SPECIFIED TOLERANCES ARE AS FOLLOWS		REVISE ONLY ON CAD SYSTEM	
G	SEE SHEET 1	C	SEE SHEET 1	INCH METRIC		TITLE	
F	SEE SHEET 1	B	SEE SHEET 1	3 PLACE ±		FLAT HEADER ASSY	
E	SEE SHEET 1	A19	SEE SHEET 1	2 PLACE ±		.156 SQ BENT PIN W/O PEG	
D	SEE SHEET 1	A17	SEE SHEET 1	1 PLACE ±		41772 SERIES DWG	
C	SEE SHEET 1	A14	SEE SHEET 1	DRAWING NUMBER AND DATE MUST REMAIN WITHIN DIMENSIONS		MOLEX INCORPORATED SHEET NO. 5 DATE 4/25/90	
B	SEE SHEET 1	A13	SEE SHEET 1	DRAWN BY: SAMEEC		FILE NAME	
A	SEE SHEET 1	A12	SEE SHEET 1	APP'D BY: LENZ		SCALE: 1:1	
LTR.	REVISIONS	LTR.	REVISIONS	COPD. BY: PATEL		PART NO. SDA-41772	
				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		REV. DATE	

13 12 11 10 9 8 7 6 5 4 3 2 1