

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:






[Molex Connector Corporation](#)
[0026613100](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

CKT	DIM. A	DIM. B
2	7.77	3.96±0.05
	3.06	.56±.002
3	11.73	7.92±0.08
	.462	.312±.003
4	15.70	11.89±0.08
	.618	.468±.003
5	19.66	15.85±0.10
	.774	.624±.004
6	23.62	19.81±0.10
	.930	.780±.004
7	27.58	23.77±0.10
	1.086	.936±.004
8	31.55	27.74±0.13
	1.242	1.092±.005
9	35.51	31.70±0.13
	1.398	1.248±.005
10	39.47	35.66±0.13
	1.554	1.404±.005
11	43.43	39.62±0.15
	1.710	1.560±.006
12	47.40	43.59±0.15
	1.866	1.716±.006
13	51.36	47.55±0.15
	2.022	1.872±.006
14	55.32	51.51±0.18
	2.178	2.028±.007
15	59.28	55.47±0.18
	2.334	2.184±.007
16	63.25	59.44±0.18
	2.490	2.340±.007
17	67.21	63.40±0.20
	2.646	2.496±.008
18	71.17	67.36±0.20
	2.802	2.652±.008

- NOTES:
 1. MATERIAL: HEADER-GLASS FILLED POLYESTER, 94V-0, MOLDED NATURAL (WHITE).
 2. FINISH:
 (154) OVERALL TIN: 0.00254/.000100 MIN OVER 0.00127/.000050 MIN NICKEL.
 (197) OVERALL REFLOWED MATTE TIN: 0.00152/.000060 MIN.
 OVER 0.00127/.000050 MIN. NICKEL OVERALL.
 (208) SELECT GOLD: 0.00038/.000015 MIN, SELECT TIN: 0.00254/.000100 MIN.
 OVERALL NICKEL UNDERPLATE: 0.00127/.000050 MIN.
 (228) SELECT GOLD: 0.00076/.000030 MIN, SELECT TIN: 0.00254/.000100 MIN.
 OVERALL NICKEL UNDERPLATE: 0.00127/.000050 MIN.
 (241) SELECT GOLD: 0.00051/.000020 MIN.
 SELECT TIN: 0.00254/.000100 MIN.
 OVERALL NICKEL UNDERPLATE: 0.00127/.000050 MIN.
 3. PRODUCT SPECIFICATION AND PROCESS PARAMETERS: SEE PS-08-50.
 4. PACKAGING: SEE CHART
 5. SOLDERABILITY: PER SMES-152.
 6. PIN PUSH-OUT FORCE: PRIOR TO SOLDERING, A 3 LB. MINIMUM FORCE (IN EITHER DIRECTION)
 7. PARTS ARE STACKABLE END TO END ON 3.96/.156 CENTERS.
 8. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.



2-*	M1
1	M1
SHEET	REV

ADD 41772-0682	2017/05/25
EC NO: UCP2012-3876	2017/05/25
DRW:KMP/PER	2017/05/25
CHKD:BEL	2017/05/25
APP:RFS/SMITH	2017/06/20
M1	REV

QUALITY SYMBOLS	DESCRIPTION
▽=0	
▽=0	
▽=0	

GENERAL TOLERANCES (UNLESS SPECIFIED)	
mm	INCH
4 PLACES ±.---	±.---
3 PLACES ±.---	±.010
2 PLACES ±0.25	±.015
1 PLACE ±0.38	±.---
ANGULAR ±1/2°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
MM/IN	
DRAWN BY	DATE
SCHAFFER	11-19-03
CHECKED BY	DATE
SAMIEC	11-21-03
APPROVED BY	DATE
MARGULIS	11-25-03
MATERIAL NO.	
SEE CHART	

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
2:1	INCH	
TITLE		
KK 156 HEADER ASSEMBLY FLAT RIGHT ANGLE SOLID BODY W/O PEGS		
Molex MOLEX INCORPORATED		
DOCUMENT NO.	SHEET NO.	
SDA-41772	1 OF *	
SIZE B THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		