

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)
[09350006207](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

1	2	3	4	5	6																																																		
A	<p style="text-align: center;">Stiftkontakt male contact</p>																																																						
B	<p style="text-align: center;">Buchsenkontakt female contact</p>																																																						
C	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Bestell-Nummer /PART NO versilbert /silverplated</th> <th>ϕ</th> <th colspan="2">Leiterquerschnitt wire gauge mm² AWG</th> <th rowspan="2">Abisolierlänge der Litze stripping length</th> </tr> </thead> <tbody> <tr> <td rowspan="5" style="writing-mode: vertical-rl; transform: rotate(180deg);">Stiftkontakt male contact</td> <td>09 35 000 6103</td> <td>1,15</td> <td>0,5</td> <td>20</td> <td rowspan="5" style="text-align: center;">6,0</td> </tr> <tr> <td>09 35 000 6104</td> <td>1,3</td> <td>0,75</td> <td>18</td> </tr> <tr> <td>09 35 000 6105</td> <td>1,45</td> <td>1,0</td> <td>18</td> </tr> <tr> <td>09 35 000 6106</td> <td>1,75</td> <td>1,5</td> <td>16</td> </tr> <tr> <td>09 35 000 6107</td> <td>2,25</td> <td>2,5</td> <td>14</td> </tr> <tr> <td rowspan="5" style="writing-mode: vertical-rl; transform: rotate(180deg);">Buchsenkontakt female contact</td> <td>09 35 000 6203</td> <td>1,15</td> <td>0,5</td> <td>20</td> <td rowspan="5" style="text-align: center;">6,0</td> </tr> <tr> <td>09 35 000 6204</td> <td>1,3</td> <td>0,75</td> <td>18</td> </tr> <tr> <td>09 35 000 6205</td> <td>1,45</td> <td>1,0</td> <td>18</td> </tr> <tr> <td>09 35 000 6206</td> <td>1,75</td> <td>1,5</td> <td>16</td> </tr> <tr> <td>09 35 000 6207</td> <td>2,25</td> <td>2,5</td> <td>14</td> </tr> </tbody> </table>						Bestell-Nummer /PART NO versilbert /silverplated	ϕ	Leiterquerschnitt wire gauge mm ² AWG		Abisolierlänge der Litze stripping length	Stiftkontakt male contact	09 35 000 6103	1,15	0,5	20	6,0	09 35 000 6104	1,3	0,75	18	09 35 000 6105	1,45	1,0	18	09 35 000 6106	1,75	1,5	16	09 35 000 6107	2,25	2,5	14	Buchsenkontakt female contact	09 35 000 6203	1,15	0,5	20	6,0	09 35 000 6204	1,3	0,75	18	09 35 000 6205	1,45	1,0	18	09 35 000 6206	1,75	1,5	16	09 35 000 6207	2,25	2,5	14
	Bestell-Nummer /PART NO versilbert /silverplated	ϕ	Leiterquerschnitt wire gauge mm ² AWG		Abisolierlänge der Litze stripping length																																																		
Stiftkontakt male contact	09 35 000 6103	1,15	0,5	20		6,0																																																	
	09 35 000 6104	1,3	0,75	18																																																			
	09 35 000 6105	1,45	1,0	18																																																			
	09 35 000 6106	1,75	1,5	16																																																			
	09 35 000 6107	2,25	2,5	14																																																			
Buchsenkontakt female contact	09 35 000 6203	1,15	0,5	20	6,0																																																		
	09 35 000 6204	1,3	0,75	18																																																			
	09 35 000 6205	1,45	1,0	18																																																			
	09 35 000 6206	1,75	1,5	16																																																			
	09 35 000 6207	2,25	2,5	14																																																			
D	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td rowspan="4" style="text-align: center;"> <p>All Dimensions in mm Original Size DIN A 4</p> </td> <td colspan="3">Techn. Character.</td> <td colspan="2">Nicht tolerierte Maßel/Free size tolerances</td> </tr> <tr> <td></td> <td style="text-align: center;">Dat.</td> <td style="text-align: center;">Name</td> <td colspan="2" rowspan="3" style="text-align: center; vertical-align: middle;"> 2:1 Han P Kontakte gedreht 16A <i>Han P contacts turned 16A</i> </td> </tr> <tr> <td></td> <td style="text-align: center;">Detail.</td> <td style="text-align: center;">ML</td> </tr> <tr> <td></td> <td style="text-align: center;">Insp.</td> <td style="text-align: center;">Be</td> </tr> <tr> <td></td> <td style="text-align: center;">Stand.</td> <td></td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">A</td> <td colspan="3">HARTING Electric GmbH & Co. KG</td> <td rowspan="2" style="text-align: center;"> </td> <td rowspan="2" style="text-align: center;"> TB 09 35 000 6... </td> </tr> <tr> <td style="text-align: center;">Mod.</td> <td style="text-align: center;">Dat.</td> <td style="text-align: center;">Name</td> <td colspan="2" style="text-align: center;"> Sub. f. TB 09 35 000 6... v. 28.03.07 </td> </tr> </table>					<p>All Dimensions in mm Original Size DIN A 4</p>	Techn. Character.			Nicht tolerierte Maßel/Free size tolerances			Dat.	Name	2:1 Han P Kontakte gedreht 16A <i>Han P contacts turned 16A</i>			Detail.	ML		Insp.	Be		Stand.				A	HARTING Electric GmbH & Co. KG				TB 09 35 000 6...	Mod.	Dat.	Name	Sub. f. TB 09 35 000 6... v. 28.03.07																		
<p>All Dimensions in mm Original Size DIN A 4</p>	Techn. Character.			Nicht tolerierte Maßel/Free size tolerances																																																			
		Dat.	Name	2:1 Han P Kontakte gedreht 16A <i>Han P contacts turned 16A</i>																																																			
		Detail.	ML																																																				
		Insp.	Be																																																				
	Stand.																																																						
A	HARTING Electric GmbH & Co. KG				TB 09 35 000 6...																																																		
Mod.	Dat.	Name	Sub. f. TB 09 35 000 6... v. 28.03.07																																																				