



Distributor of Harting: Excellent Integrated System Limited

Datasheet of 09642217210 - D-Sub Connector Plug, Male Pins 15 Position Free Hanging (In-Line) Solder Cup

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)

[09642217210](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

5		3	2	1																																																									
D				1																																																									
C	<p style="text-align:center;">Solder buckets for AWG 20 Max</p>			1																																																									
B	<p style="text-align:right;">SPECIFICATION</p> <table style="width:100%; border-collapse: collapse;"> <tr> <td>Performance level</td> <td>PL2</td> </tr> <tr> <td>Filter type</td> <td>C</td> </tr> <tr> <td>Capacitance</td> <td>47pf±20%</td> </tr> <tr> <td>Working Voltage</td> <td>100v</td> </tr> <tr> <td>Current Rating</td> <td>7,5A</td> </tr> <tr> <td>Insulation Resistance</td> <td>>1GΩ</td> </tr> </table> <table border="1" style="width:100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width:50%;">FREQUENCY (MHz)</th> <th style="width:50%;">ATTENUATION dB</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>-</td> </tr> <tr> <td>10</td> <td>-</td> </tr> <tr> <td>50</td> <td>-</td> </tr> <tr> <td>100</td> <td>-</td> </tr> <tr> <td>500</td> <td>30dB</td> </tr> <tr> <td>1000</td> <td>35dB</td> </tr> </tbody> </table>			Performance level	PL2	Filter type	C	Capacitance	47pf±20%	Working Voltage	100v	Current Rating	7,5A	Insulation Resistance	>1GΩ	FREQUENCY (MHz)	ATTENUATION dB	5	-	10	-	50	-	100	-	500	30dB	1000	35dB	1																															
Performance level	PL2																																																												
Filter type	C																																																												
Capacitance	47pf±20%																																																												
Working Voltage	100v																																																												
Current Rating	7,5A																																																												
Insulation Resistance	>1GΩ																																																												
FREQUENCY (MHz)	ATTENUATION dB																																																												
5	-																																																												
10	-																																																												
50	-																																																												
100	-																																																												
500	30dB																																																												
1000	35dB																																																												
A	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> </tr> <tr> <td></td> <td></td> <td></td> <td>Detail.</td> <td>8-JUL-02</td> <td>CV</td> <td rowspan="2" style="text-align:center; vertical-align:middle;"> <small>All Dim. in mm Orig. Size DIN A 4</small> </td> <td rowspan="2" style="text-align:center; vertical-align:middle;"> D-Sub, male, straight 15 Poles, solder buckets, with dimples and holes </td> <td rowspan="2" style="text-align:center; vertical-align:middle;"> <small>Mo/No/Tab/ Scale</small> 1.5:1 </td> </tr> <tr> <td></td> <td></td> <td></td> <td>Insp.</td> <td>12/01/12</td> <td>JB</td> </tr> <tr> <td></td> <td>36283</td> <td>12/01/12</td> <td>SD</td> <td>Stand.</td> <td></td> <td></td> <td rowspan="3" style="text-align:center; vertical-align:middle;"> TB 09642217210 </td> <td rowspan="3" style="text-align:center; vertical-align:middle;"> <small>Blatt/ Page</small> 1 / 1 </td> </tr> <tr> <td></td> <td>33267</td> <td>17/11/05</td> <td>JMDR</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>31058</td> <td>8-JUL-02</td> <td>CV</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Mod.</td> <td>Det.</td> <td>Name</td> <td colspan="3" style="text-align:center;"> HARTING EURL F-95972 Paris </td> <td style="text-align:center;">Sub.</td> <td></td> </tr> </table>																Detail.	8-JUL-02	CV	 <small>All Dim. in mm Orig. Size DIN A 4</small>	D-Sub, male, straight 15 Poles, solder buckets, with dimples and holes	<small>Mo/No/Tab/ Scale</small> 1.5:1				Insp.	12/01/12	JB		36283	12/01/12	SD	Stand.			TB 09642217210 	<small>Blatt/ Page</small> 1 / 1		33267	17/11/05	JMDR					31058	8-JUL-02	CV					Mod.	Det.	Name	HARTING EURL F-95972 Paris			Sub.		1
			Detail.	8-JUL-02	CV	 <small>All Dim. in mm Orig. Size DIN A 4</small>	D-Sub, male, straight 15 Poles, solder buckets, with dimples and holes	<small>Mo/No/Tab/ Scale</small> 1.5:1																																																					
			Insp.	12/01/12	JB																																																								
	36283	12/01/12	SD	Stand.			TB 09642217210 	<small>Blatt/ Page</small> 1 / 1																																																					
	33267	17/11/05	JMDR																																																										
	31058	8-JUL-02	CV																																																										
	Mod.	Det.	Name	HARTING EURL F-95972 Paris			Sub.																																																						