



Distributor of Harting: Excellent Integrated System Limited

Datasheet of 09642227800 - D-Sub Connector Plug, Male Pins 15 Position Through Hole Solder

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)

[09642227800](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Technical drawing showing dimensions for the D-Sub connector plug. Dimensions include: 33,3 ± 0,2, 8,3 ± 0,3, 12,5 ± 0,3, 25,25 ± 0,2, 2,77, 39,2 ± 0,3, 27,7 ± 0,3, 2,8, 6 ± 0,3, 4,2, 2,84, 33,3, 1,385, 2,77, φ 3,1, φ 1 ± 0,05, φ 3,2 ± 0,05, φ 0,1, 0,25 A, 0,25 B.

SPECIFICATIONS

FREQUENCY (MHz)	ATTENUATION (dB)
5	0,5
10	1
50	3,5
100	4
500	5
1000	5,5

Operating voltage < 250 V AC
 Working current < 7,5 A
 Insulation resistance > 16Ω
 Contact resistance < 15 mΩ
 Dielectric withstanding voltage 500 V AC / minute

PCB layout, component side

D-Sub, male, straight, 15 poles, tin plated shell with dimples, solder pins, ferrite filter

All Dim. in mm
 Orig. Size DIN A 4

			Det.	Name		TB 09 64 222 7800 Sub.	Maßstab/ Scale 1,5:1 Blatt/ Page 1 / 1	
			Detail.	11/06/09				PK
			Insp.					
			Stand.					
36160	22/09/10	SC	HARTING EURL			TB 09 64 222 7800 Sub.	Blatt/ Page 1 / 1	
09 64 222 7800	PL3	EC00332	11/06/09	PK				F-95972 Paris
Part number	Performance level	Mod.	Det.	Name				