

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190180011

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190180011 - Connector Quick Connect Receptacle 14-16 AWG 0.187" (4.75mm) Crimp

one company > a world of innovation

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190180011 Status: Active Standard Quick-Disconnect Terminals **Overview: Description:** VibraKrimp™ Quick Disconnect, Female, for 14-16 (2.00-1.30mm²) Wire, Box, Tab 4.75 x 0.51mm **Documents:** Drawing (PDF) Product Specification PS-19902-013 (PDF) Product Specification PS-19902-005 (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-19902-011 (PDF) Series image - Reference only **Agency Certification** LR18689 CSA EU ELV Not Relevant UL E79133 General EU RoHS China RoHS **Product Family Quick Disconnects** Compliant REACH SVHC Series 19018 Butted Seam Not Contained Per Comments Crimp Quality Equipment -ED/79/2015 (17 Yes Insulated No December 2015) Overview Standard Quick-Disconnect Terminals Halogen-Free Product Name VibraKrimp™ Status Type UPC Quick Disconnect Low-Halogen 800755048179 Need more information on product environmental compliance? Physical Barrel Type Closed Email productcompliance@molex.com Female Gender Please visit the Contact Us section for any Glow-Wire Compliant No non-product compliance questions. Insulation None China ROHS Green Image Lock to Mating Part None Material - Metal Brass ELV Not Relevant Material - Plating Mating Tin Material - Plating Termination Tin Net Weight 0.598/g Search Parts in this Series Straight Orientation 19018 Series Packaging Type Bag Polarized to Mating Part No Application Tooling | FAQ Tab Thickness 0.51mm Tooling specifications and manuals are Tab Width 4.75mm found by selecting the products below. Temperature Range - Operating Per Wire Specification Crimp Height Specifications are then Wire Insulation Diameter 2.10-3.70mm contained in the Application Tooling Wire Size AWG 14.16 Specification document. Wire Size mm<sup>2</sup> 1.30-2.00 Global Electrical Description Product # Air Powered Crimp 0640077300 Voltage - Maximum Per Wire Specification Tool Head Material Info Hand Crimp Tool 0640037200 BB-4174 Old Part Number Right Hand Crimp 0640037300 Tool for Female Non-**Reference - Drawing Numbers** Insulated Standard PS-19902-005, PS-19902-011, PS-19902-013 **Product Specification** Quick Disconnects. Sales Drawing SD-19018-001 12-16 AWG Wire



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190180011 - Connector Quick Connect Receptacle 14-16 AWG 0.187" (4.75mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com Website: www.integrated-c

This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION