

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190090007

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



nc

**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190090007 - Connector Quick Connect Receptacle 18-22 AWG 0.250" (6.35mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

one company > a world of innovation This document was generated on 07/28/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190090007 Status: Active Standard Quick-Disconnect Terminals **Overview: Description:** VibraKrimp<sup>™</sup> Quick Disconnect Flag, Female, for 18-22 AWG Wire, Metal Strip Carrier **Documents:** Drawing (PDF) RoHS Certificate of Compliance (PDF) Packaging Specification PK-19009-001 (PDF) Agency Certification Series image - Reference only LR18689 CSA UL E79133 EU ELV General Not Relevant Quick Disconnects Product Family Series <u>19009</u> EU RoHS China RoHS Comments Wire Grip Compliant REACH SVHC Crimp Quality Equipment Yes Not Contained Per Insulated No Standard Quick-Disconnect Terminals -ED/79/2015 (17 Overview Product Name VibraKrimp™ December 2015) **Quick Disconnect** Туре Halogen-Free UPC 800755046854 Status Low-Halogen Physical Need more information on product Barrel Type Closed environmental compliance? Gender Female **Glow-Wire Compliant** No Email productcompliance@molex.com Insulation None Please visit the Contact Us section for any Lock to Mating Part None non-product compliance questions. Material - Metal Brass China ROHS Green Image Material - Plating Mating Tin Material - Plating Termination ELV Not Relevant Tin Net Weight 0.488/g Orientation Flag Packaging Type Reel Search Parts in this Series Polarized to Mating Part No 19009 Series Tab Thickness 0.81mm Tab Width 6.35mm Application Tooling | FAQ Temperature Range - Operating Per Wire Specification Tooling specifications and manuals are Wire Insulation Diameter 3.43mm found by selecting the products below. Wire Size AWG 18, 20, 22 Crimp Height Specifications are then contained in the Application Tooling Electrical Specification document. Voltage - Maximum Per Wire Specification Global Material Info Description Product # Old Part Number AAZ-4168 Mini-Mac™ 0638027400 Applicator Rear Feed **Reference - Drawing Numbers** ASP Perishable 0190290128 Packaging Specification PK-19009-001 Tool Kit used in ASP CDFGS250 Sales Drawing presses that process metal strip product

This document was generated on 07/28/2016



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190090007 - Connector Quick Connect Receptacle 18-22 AWG 0.250" (6.35mm) Crimp

PLEASE CHECK WWW MOLEX COM FOR LATEST PART INFORMATION