

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190160100

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190160100 - Connector Quick Connect Receptacle 24-26 AWG 0.187" (4.75mm) Crimp

one company > a world of innovation

<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION			
Part Number:	0190160100		
Status:	Active		
Overview: Standard Quick-Disconn			
Description:		nect, Female, for 24-26 (0.20-0.12mm ²) Wire, Mylar Tape,	
	Tab 4.75 x 0.51mm		
Documents:			
Drawing (PDF)		Product Specification PS-19902-015 (PDF)	
Product Specification	<u>n PS-19902-011 (PDF)</u>	RoHS Certificate of Compliance (PDF)	
			-
General			Series image - Reference only
Product Family		Quick Disconnects	
Series		19016	EU ELV
Comments		Butted Seam	Not Relevant
Crimp Quality Equipr	ment	Yes	
Insulated		No	EU RoHS China RoHS
Overview		Standard Quick-Disconnect Terminals	Compliant
Product Name		Krimptite™	REACH SVHC
Type		Quick Disconnect	Not Contained Per
UPC		800753035157	-ED/79/2015 (17
010			December 2015)
Physical			Halogen-Free
Barrel Type		Closed	Status
Gender		Female	Low-Halogen
Glow-Wire Compliant		No	Need more information on product
Insulation		None	environmental compliance?
Lock to Mating Part		None	
Material - Metal		Brass	Email productcompliance@molex.com
Material - Plating Mating		Tin	Please visit the Contact Us section for any
Material - Plating Termination		Tin	non-product compliance questions.
Net Weight		0.360/g	
Orientation		Straight	China ROHS Green Image
Packaging Type		Adhesive Tape on Reel	ELV Not Relevant
Plating min - Mating		2.540µm	
Plating min - Termina	ation	2.540µm	
Polarized to Mating Part		No	Search Parts in this Series
Tab Thickness		0.51mm	19016 Series
Tab Width		4.75mm	
Temperature Range - Operating		Per Wire Specification	Application Tables - 540
Termination Interface		Crimp or Compression	Application Tooling FAQ
Wire Size AWG	5. Gtyle	24, 26	Tooling specifications and manuals are
WING DIZE AWD		27,20	found by selecting the products below.
Electrical			Crimp Height Specifications are then
Voltage - Maximum		Per Wire Specification	contained in the Application Tooling
-			Specification document.
Material Info			Global
Old Part Number		M-1136T	Description Product #
Defense D			ATP Crimp Dies <u>0190270178</u>
Reference - Drawin		D0 40000 044 D0 40000 045	for the Tape Crimp
Product Specification	1	PS-19902-011, PS-19902-015	Module and ATP-101
Sales Drawing		SD-19016-004	& 301 Press

This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION