

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190030086

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030086 - Connector Quick Connect Receptacle 14-16 AWG 0.205" (5.21mm) Crimp

one company > a world of innovation

<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

Part Number:	0190030086			
tatus:				*
	Active			Mr y /
verview:	Standard Quick-Disconne			
escription:		nnect, Female, for 14-16 (2.00-1.30mm ²), Continuous Molded		
	Strip, Tab 5.21 x 0.81mm			A SERRATIONS STRESSRELIEVED BARREL
_				BARREL
Documents:				STOP
<u>3D Model</u>		Product Specification PS-19902-011 (PDF)	>	MOLDED NYLON INSULATED HOUSING
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		INSOCATED HOOSING
Product Specification F	<u> PS-19902-008 (PDF)</u>		o · · ·	
			Series ima	ge - Reference only
Agency Certification				
UL		E79133	<u>EU ELV</u>	
General			Not Relevant	
Product Family		Quick Disconnects		China RoHS
Series		<u>19003</u>	EU RoHS	China Kona
Comments			Compliant	
	t	Funnel Entry	REACH SVHC	
Crimp Quality Equipme	#11L	Yes Fully	Not Contained Per	
Overview		Fully Standard Quick-Disconnect Terminals	-ED/79/2015 (17	
		InsulKrimp™	December 2015)	
Product Name		Quick Disconnect	Halogen-Free	
Type UPC		800755961379	<u>Status</u>	
UPC		800755961379	Low-Halogen	
Physical				nation on product
Barrel Type		Closed	environmental co	mpliance?
Color - Resin		Blue	Email productcom	pliance@molex.com
Flammability		94V-2		ntact Us section for any
Gender		Female	non-product comp	
Glow-Wire Compliant		Yes		lance questions.
Insulation		Nylon (PA)	China ROHS	Not Relevant
Lock to Mating Part		None	ELV	Not Relevant
Material - Metal		Brass	[[
Material - Plating Matir	DI	Tin		
Material - Plating Term		Tin		
Material - Resin	ination	Nylon	Search Parts in	this Series
Net Weight		0.728/g	<u>19003</u> Series	
Orientation		Straight		
Packaging Type		Reel	Application Too	
Plating min - Mating		4.064µm		tions and manuals are
Plating min - Terminati	on	4.064µm		ng the products below.
Polarized to Mating Pa		Νο		ecifications are then
Tab Thickness		0.81mm		Application Tooling
Tab Width		5.21mm	Specification do	cument.
Temperature Range - (Operating	-65°C to +105°C	Global	
Termination Interface:		Crimp or Compression	Description	Product #
Wire Insulation Diamet	5	4.06mm max.	Mini-Mac™	0638834200
Wire Size AWG		14, 16	Applicator	
Wire Size mm ²		1.30-2.00	ACP Perishable	<u>0190280040</u>
		1.00 2.00	Tool Kit used in .	ACP
Electrical			presses that pro	cess
Voltage - Maximum		600V	continuous mold	ed
C			product	
Material Info			, <u></u>	
Old Part Number		BB-2216C		



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030086 - Connector Quick Connect Receptacle 14-16 AWG 0.205" (5.21mm) Crimp

Product Specification Sales Drawing Contact us: sales@PS-19902-008_PS-19902-011 SD-19063-005 Contact us: sales@pression of the second se

This document was generated on 03/04/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION