Distributor of Molex Connector Corporation: Excellent Integrated System Limited
Datasheet of 0190030022 - Connector Quick Connect Receptacle 18-22 AWG 0.187"
(4.75mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190030022

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of Molex Connector Corporation: Excellent Integrated System Limited

Datasheet of 0190030022 - Connector Quick Connect Receptacle 18-22 AWG 0.187" (4.75mm) Crimp



Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/02/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0190030022 Status: **Active**

Standard Quick-Disconnect Terminals Overview:

Description: InsulKrimp™ Quick Disconnect, Female, for 18-22 (0.80-0.35mm²), Continuous Molded

Strip, Tab 4.75 x 0.81mm

Documents:

Product Specification PS-19902-011 (PDF) 3D Model Drawing (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-19902-008 (PDF)

Agency Certification

LR18689 CSA UL E79133

General

Product Family Quick Disconnects

Series 19003 Funnel Entry Comments Crimp Quality Equipment Yes Insulated Fully

Overview Standard Quick-Disconnect Terminals

InsulKrimp™ **Product Name** Type UPC Quick Disconnect 800753028753

Physical Barrel Type Closed Color - Resin Red 94V-2 Flammability Gender Female Glow-Wire Compliant Yes Insulation Nylon (PA) Lock to Mating Part None Material - Metal Brass Material - Plating Mating Tin

Material - Plating Termination Tin Material - Resin Nvlon Net Weight 0.842/q Orientation Straight Packaging Type Reel Plating min - Mating 4.064µm Plating min - Termination Polarized to Mating Part 4.064µm No Tab Thickness 0.81mm Tab Width 4.75mm

Temperature Range - Operating -65°C to +105°C Termination Interface: Style Crimp or Compression Wire Insulation Diameter 5.84mm max. 18, 20, 22

Wire Size AWG


600V Voltage - Maximum

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Electrical



Series image - Reference only

EU ELV Not Relevant

EU RoHS **China RoHS**

REACH SVHC Not Contained Per -ED/108/2014 (17 Dec

2014) Halogen-Free **Status** Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

19003 Series

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # Mini-Mac™ 0638837200 Applicator



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190030022 - Connector Quick Connect Receptacle 18-22 AWG 0.187"

(4.75mm) Crimp

Old Part Number Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Reference - Drawing Numbers

PS-19902-008, PS-19902-011

Product Specification Sales Drawing

SD-19003-006

This document was generated on 03/02/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION