

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190250010

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



**Distributor of Molex Connector Corporation: Excellent Integrated System Limited** Datasheet of 0190250010 - Connector Quick Connect Tab 14-16 AWG 0.250" (6.35mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

one company > a world of innovation

art Number:	0190250010		
tatus:			
	Active		
verview:	Standard Quick-Disconn		
escription:		nect, Male, for 14-16 (2.00-1.30mm <sup>2</sup> ) Wire, Mylar Tape, Tab	
	6.35 x 0.81mm		
Documents:			
Drawing (PDF)		Product Specification PS-19902-015 (PDF)	
	n PS-19902-011 (PDF)	RoHS Certificate of Compliance (PDF)	
	n PS-19902-014 (PDF)		
			Series image - Reference only
Agency Certificatio	n	1.5.4000	
CSA		LR18689	<u>EU ELV</u>
JL		E79133	Not Relevant
General			EU RoHS China RoHS
Product Family		Quick Disconnects	Not Reviewed
Series		19025	REACH SVHC
Comments		Funnel Ferrule Entry	Not Reviewed
Crimp Quality Equip	ment	Yes	Halogen-Free
nsulated		Partial	Status
Overview		Standard Quick-Disconnect Terminals	Not Reviewed
Product Name		Avikrimp™	Need more information on product
Гуре		Quick Disconnect	environmental compliance?
JPC		800753040533	
Dhusiaal			Email productcompliance@molex.com
<b>Physical</b> Barrel Type		Closed	Please visit the <u>Contact Us</u> section for an
Color - Resin		Closed Blue	non-product compliance questions.
Flammability		94V-2	China ROHS Not Reviewed
Gender		Male	ELV Not Relevant
Glow-Wire Compliar	t .	No	
Insulation	it.	Nylon (PA)	
Lock to Mating Part		None	
Material - Metal		Brass	Search Parts in this Series
Material - Plating Ma	ıtina	Zinc Chromate	<u>19025</u> Series
Material - Plating Te		Zinc Chromate	
Material - Resin		Nylon	Use With
Net Weight		1.369/g	<u>19002-0025</u>
Drientation		Straight	
Packaging Type		Adhesive Tape on Reel	Application Tooling   FAQ
Polarized to Mating	Part	No	Tooling specifications and manuals are
Tab Thickness		0.81mm	found by selecting the products below.
Tab Width		6.35mm	Crimp Height Specifications are then
Cemperature Range		-65°C to +105°C	contained in the Application Tooling
Nire Insulation Diam	neter	4.30mm max.	Specification document.
Nire Size AWG		14, 16	Global Description Broduct #
Vire Size mm <sup>2</sup>		1.30-2.00	Description Product #   Mini-Mac <sup>™</sup> 0638853400
Electrical			Applicator
/oltage - Maximum		600V	ATP Crimp Dies 0192880085
0			for the Tape Crimp
Material Info			Module and ATP-101
Old Part Number		MCT-5T	& 301 Press
Reference - Drawin	g Numbers		,
Product Specification		PS-19902-011, PS-19902-014, PS-19902-015	
Sales Drawing		SD-19025-002	



Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/08/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION