

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190070026

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190070026 - Connector Quick Connect Receptacle 14-16 AWG 0.250" (6.35mm) Crimp

one company) a world of innovation

<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

This document was generated on 03/28/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION			
Part Number:	19007-0026		-
Status:			
	Active		
Description:	Tape, Tab 6.35 x 0.81mm	Disconnect, Female, for 14-16 (2.00-1.30mm²) Wire, Mylar ו	CALLY .
Documents:			
Drawing (PDF)		Product Specification PS-19902-015 (PDF)	
Product Specificat	tion PS-19902-008 (PDF)	RoHS Certificate of Compliance (PDF)	
Product Specificat	tion PS-19902-011 (PDF)		Series
Agency Certif	ication		image - Reference only
CSA		LR18689	
UL		E79133	EU RoHS China RoHS
General			Compliant
Product Family		Quick Disconnects	REACH SVHC
Series		19007	Not Reviewed
Crimp Quality Equipment		<u>19007</u> Yes	Low-Halogen Status
Product Name	ipment	InsulKrimp™	Not Reviewed
		Quick Disconnect	NOT Reviewed
Туре		Quick Disconnect	Need more information on product environmental compliance?
Physical			environmental compliance?
Barrel Type		Closed	Email productcompliance@molex.com
Color - Resin		Natural	For a multiple part number RoHS Certificate
Flammability		94V-2	Compliance, click here
Gender		Female	
Glow-Wire Compliant		No	Please visit the <u>Contact Us</u> section for any
nsulation		Nylon (PA)	non-product compliance questions.
Lock to Mating Part		None	
Material - Metal		Brass	
Material - Resin		Nylon	
Orientation		Flag	Search Parts in this Series
Packaging Type		Adhesive Tape on Reel	<u>19007</u> Series
Polarized to Matin	g Part	No	
Tab Thickness		0.81mm	Application Tooling FAQ
Tab Width		6.35mm	Tooling specifications and manuals are
Temperature Ran	ge - Operating	-65°C to +105°C	found by selecting the products below.
Wire Insulation Diameter		6.73mm max.	Crimp Height Specifications are then
Wire Size AWG		14, 16	contained in the Application Tooling
Wire Size mm ²		1.30 - 2.00	Specification document.
Electrical			Global
Voltage - Maximum		600V	Description Product # Crimp Dies for 0192880165
Material Info			the ATP-301 Air
Old Part Number		BB-2221XT	Crimping Press for Mylar Tape Mounted
	rawing Numbers		Terminals
Product Specificat		PS-19902-008, PS-19902-011, PS-19902-015	
Sales Drawing		SD-19007-004	

This document was generated on 03/28/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION