

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190240001

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



one company > a world of innovation

ex[,]

mo

Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190240001 - Connector Quick Connect Tab 18-22 AWG 0.250" (6.35mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION			
Part Number:	0190240001		
status:	Active		_
verview:	Standard Quick-Disconn		
escription:	VibraKrimp™ Quick Disc 0.81mm	connect, Male, for 18-22 (0.80-0.35mm ²) Wire, Box, Tab 6.35 x	
	0.81mm		
Documents:			
Drawing (PDF)		Product Specification PS-19902-013 (PDF)	
Product Specificat	ion PS-19902-005 (PDF)	RoHS Certificate of Compliance (PDF)	Series image - Reference only
Product Specificat	ion PS-19902-011 (PDF)		· · · · ·
			EU ELV
General			Not Relevant
Product Family		Quick Disconnects	
Series		<u>19024</u>	EU RoHS China RoHS
Comments		Brass Sleeve with Funnel Ferrule Entry	Compliant
Crimp Quality Equ	ipment	Yes	REACH SVHC
Insulated		No	Not Contained Per
Overview		Standard Quick-Disconnect Terminals	-ED/79/2015 (17
Product Name		VibraKrimp™	December 2015)
Туре		Quick Disconnect	Halogen-Free
UPC		800753040274	<u>Status</u>
Diversional			Low-Halogen
Physical			Need more information on product
Barrel Type		Closed	environmental compliance?
Gender		Male	Email productcompliance@molex.com
Glow-Wire Compliant		No	Please visit the Contact Us section for an
Insulation		None	non-product compliance questions.
Lock to Mating Part		None	non-product compliance questions.
Material - Metal Material - Plating Mating		Brass	China ROHS Green Image
		Zinc Chromate Zinc Chromate	ELV Not Relevant
Material - Plating Termination Net Weight			
Orientation		1.107/g Straight	
Packaging Type		Bag	Search Parts in this Series
Polarized to Mating Part		No	19024 Series
Tab Thickness	gran	0.81mm	
Tab Width		6.35mm	Annihastian Tasling FAC
Temperature Rang	re - Operating	Per Wire Specification	Application Tooling FAQ
Wire Insulation Dia		3.60mm max.	Tooling specifications and manuals are
Wire Size AWG		18, 20, 22	found by selecting the products below. Crimp Height Specifications are then
		, _ • ,	contained in the Application Tooling
Electrical			Specification document.
Voltage - Maximur	n	Per Wire Specification	Global
Material Info			Description Product #
Old Part Number		AMCT-4	Hand Crimp Tool 0640016600
Reference - Draw	ing Numbers		Crimp Head for the <u>0640056600</u>
Product Specificat		PS-19902-005, PS-19902-011, PS-19902-013	AT-200 [™] Pneumatic
Sales Drawing		PS-19902-005, PS-19902-011, PS-19902-013 SD-19024-001	Hand Tool

This document was generated on 03/04/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION