

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0190070083

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190070083 - Connector Quick Connect Receptacle 10-12 AWG 0.250" (6.35mm) Crimp



<u>Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com</u>

This document was generated on 03/01/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION Part Number: 0190070083 Status: Active Standard Quick-Disconnect Terminals **Overview:** InsulKrimp[™] Female Fully Insulated Quick Disconnect Flag for 10-12 AWG Wire, Tab **Description:** 6.35 x 0.81mm, 94 V-0 Material, Mylar Tape Carrier **Documents:** Product Specification PS-19902-011 (PDF) 3D Model Drawing (PDF) Product Specification PS-19902-015 (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-19902-008 (PDF) Series image - Reference only Agency Certification E79133 UL EU ELV Not Relevant General **Product Family** Quick Disconnects EU RoHS China RoHS 19007 Series Compliant Crimp Quality Equipment REACH SVHC Yes . Insulated Fully Not Contained Per Standard Quick-Disconnect Terminals Overview -ED/79/2015 (17 Product Name InsulKrimp™ December 2015) **Quick Disconnect** Туре Halogen-Free UPC 800756386874 Status Not Low-Halogen Physical Need more information on product Barrel Type Closed environmental compliance? Color - Resin Yellow Flammability 94V-0 Email productcompliance@molex.com Female Gender Please visit the Contact Us section for any Glow-Wire Compliant Yes non-product compliance questions. Insulation Nylon (PA) China ROHS Green Image Lock to Mating Part None Material - Metal ELV Not Relevant Brass Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon Search Parts in this Series Net Weight 1.601/g 19007 Series Orientation Flag Adhesive Tape on Reel Packaging Type Application Tooling | FAQ Polarized to Mating Part No Tooling specifications and manuals are Tab Thickness 0.81mm found by selecting the products below. Tab Width 6.35mm Crimp Height Specifications are then Temperature Range - Operating -65°C to +105°C contained in the Application Tooling Wire Insulation Diameter 6.60mm Specification document. Wire Size AWG 10 (105 strands), 12 (65 strands) Global Electrical Description Product # ATP Perishable Tool 0198032010 600V Voltage - Maximum Kit. used in ATP Solder Process Data Presses that Process Lead-freeProcess Capability N/A Product on Tape Material Info Old Part Number C-2211VT **Reference - Drawing Numbers** Product Specification PS-19902-008, PS-19902-011, PS-19902-015 Sales Drawing SD-19007-002



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0190070083 - Connector Quick Connect Receptacle 10-12 AWG 0.250" (6.35mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/01/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION