

Distributor of Molex Connector Corporation: Excellent Integrated System Limited
Datasheet of 0191640018 - Connector Quick Connect Receptacle 18-22 AWG 0.250"
(6.35mm) Crimp

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0191640018

For any questions, you can email us directly: sales@integrated-circuit.com



## Distributor of Molex Connector Corporation: Excellent Integrated System Limited

Datasheet of 0191640018 - Connector Quick Connect Receptacle 18-22 AWG 0.250" (6.35mm) Crimp

molex°
one company > a world of innovation

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

This document was generated on 03/08/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>0191640018</u>

Status: Active

Overview: Perma-Seal™ Terminals

Description: Perma-Seal™ Female Quick Disconnect Receptacle for 18-22 AWG Wire, Tab Size

6.35 x 0.81mm, Mylar Tape Carrier

**Documents:** 

Drawing (PDF)
Product Specification PS-19902-011 (PDF)
Product Specification PS-19902-011 (PDF)
Product Specification PS-19902-011 (PDF)
ROHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR18689 UL E79133

General

Product Family Quick Disconnects

Series 19164
Crimp Quality Equipment Yes
Insulated Fully

Overview <u>Perma-Seal™ Terminals</u>

 Product Name
 Perma-Seal™

 Type
 Quick Disconnect

 UPC
 800753113060

**Physical** 

Barrel Type Closed Color - Resin Red Gender Female Glow-Wire Compliant No NiAc™ Insulation Lock to Mating Part None Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon Net Weight 1.733/g Orientation Straight

Packaging Type Adhesive Tape on Reel

 Tab Thickness
 0.81mm

 Tab Width
 6.35mm

 Temperature Range - Operating
 -55°C to +125°C

 Wire Insulation Diameter
 4.32mm max.

 Wire Size AWG
 18, 20, 22

Electrical

Voltage - Maximum 600V

Material Info

Old Part Number SAA-9261T

**Reference - Drawing Numbers** 

Product Specification PS-19902-011, PS-19902-015

Sales Drawing SD-19164-020

Series image - Reference only

EU ELV Not Relevant

EU RoHS China RoHS Compliant

REACH SVHC Not Contained Per -ED/108/2014 (17 Dec

2014)
Halogen-Free
Status
Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

19164 Series

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

DescriptionProduct #ATP Crimp Dies0192880095for the Tape Crimp

Module and ATP-101 & 301 Press

This document was generated on 03/08/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION