

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 5020781360

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 5020781360 - CONN FPC BOTTOM 13POS 0.25MM R/A Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

molex[®] one company > a world of innovation

This document was generated on 07/13/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION				
Part Number:	5020781360			
Status:	Active) x
Overview:	FFC-FPC (SMT)			
Description:	,	0.25mm Pitch Easy-On™ Type FPC Connector, 1.00mm Mated Height, Right Angle, Surface Mount, Bottom Contact Style, with Extended Actuator, 13 Circuits, Halogen-		
	Free	Contact Style, with Extended Actuator, 13 Circuits, Halogen-		HADR (D))
	Fiee			
Documents:				XXX /
3D Model		RoHS Certificate of Compliance (PDF)	τα.	
Drawing (PDF)		<u>Rono Certificate of Compliance (FDF)</u>		
			Series ima	ge - Reference only
General				
Product Family		FFC/FPC Connectors	EU ELV	
Series		<u>502078</u>	Not Relevant	
Overview		FFC-FPC (SMT)		
Product Name		Easy-On™	EU RoHS	China RoHS
UPC		884982250109	Compliant	
			REACH SVHC	
Physical			Not Contained Pe	r -
Circuits (Loaded)		13	ED/21/2016 (20 Ju	ine
Contact Position		Bottom	2016)	
Durability (mating cycles max)		10	Halogen-Free	
Entry Angle		90° Angle	Status	
Mated Height		1.00mm	Low-Halogen	
Material - Metal		Phosphor Bronze	Need more information on product	
Material - Plating Mating		Gold	environmental co	ompliance?
Material - Plating Te	rmination	Gold		
Net Weight		23.510/mg	Email productcompliance@molex.com	
Number of Rows		1	Please visit the <u>Contact Us</u> section for any non-product compliance questions.	
Orientation		Right Angle	non-product comp	nance questions.
PCB Locator		No	China ROHS	Green Image
PCB Retention		Yes	ELV	Not Relevant
Packaging Type		Embossed Tape on Reel	1	
Pitch - Mating Interfa	ace	0.25mm		
Polarized to PCB		Yes		4. 0.
Stackable		No	Search Parts in this Series	
Temperature Range - Operating Termination Interface: Style		-20°C to +85°C	502078 Series	
Wire/Cable Type	e. Siyie	Surface Mount FPC only		
Electrical	0			
Current - Maximum per Contact		0.2A		
Voltage - Maximum		50V		
Material Info				
Reference - Drawin	g Numbers			
Sales Drawing		5020780000, 5020781000		

This document was generated on 07/13/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION