

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151660071

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## K one company > a world of innovation

This document was generated on 07/11/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION				
Status:AOverview:PrDescription:0.5	O151660071   Active   Premo-Flex™ Cable Jumpers   0.50mm Pitch Premo-Flex™ FFC Jumper, Same Side Contacts (Type A), 6 Circuits,   0.305m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating			
Documents: Drawing (PDF) Packaging Specification P	K-15166-001 (PDF)	RoHS Certificate of Compliance (PDF)		
General			Series image - Reference only	
Product Family Series Comments		Cable <u>15166</u> Contacts on the same side, Type A	EU ELV Not Reviewed	
Crimp Quality Equipment Overview Product Name		Yes <u>Premo-Flex™ Cable Jumpers</u> Premo-Flex™FFC Jumper	EU RoHS China RoHS Not Reviewed	
UPC Physical		884982845633	REACH SVHC Not Reviewed Halogen-Free	
Cable Length Circuits (Loaded)		0.305m 6	Status Not Reviewed	
Circuits (maximum) Net Weight Packaging Type		6 1.000/g Bag	Need more information on product environmental compliance?	
Pitch - Termination Interfa Temperature Range - Ope Wire Size AWG		0.50mm -40°C to +105°C N/A	Email <u>productcompliance@molex.com</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions.	
Wire/Cable Type		Flat Flex Cable	China ROHS Not Reviewed ELV Not Reviewed	
Current - Maximum per Co Voltage - Maximum	ontact	0.5A 60V AC	,	
Material Info			Search Parts in this Series 15166 Series	
Reference - Drawing Nur Packaging Specification	nbers	PK-15166-001	Use With	

Packaging Specification Sales Drawing

PK-15166-001 SD-15166-001

<a href="http://www.molex.com/product/ ffcfpc\_th.html">Molex FFC - FPC connector</a>. Be sure to match like plating

This document was generated on 07/11/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION