

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151660124

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0151660124 - FFC 0.50 TYPE D 12 CKTS LGT 102 Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

K one company > a world of innovation

Sales Drawing

| PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION | | | |
|--|--|---------------------------------------|--|
| Part Number: | <u>0151660124</u> | | |
| Status: | Active | | |
| Overview: Premo-Flex™ Cal | | Jumpers | |
| Description: | 0.50mm Pitch Premo-Flex [™] FFC Jumper, Opposite Side Contacts (Type D), 12 | | |
| | Circuits, 0.102m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating | | |
| Documents: | | | |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | |
| Packaging Specific | ation PK-15166-001 (PD | <u>)</u> | |
| General | | | Series image - Reference only |
| Product Family | | Cable | |
| Series | | <u>15166</u> | EU ELV |
| Comments | | Contacts on opposite sides, Type D | Not Reviewed |
| Crimp Quality Equipment | | Yes | |
| Overview | | Premo-Flex [™] Cable Jumpers | EU RoHS China RoHS |
| Product Name | | Premo-Flex™FFC Jumper | Not Reviewed |
| UPC | | 884982846166 | REACH SVHC |
| | | | Not Reviewed |
| Physical | | | Halogen-Free |
| Cable Length | | 0.102m | <u>Status</u> |
| Circuits (Loaded) | | 12 | Not Reviewed |
| Circuits (maximum) | | 12 | Need more information on product |
| Net Weight_ | | 1.000/g | environmental compliance? |
| Packaging Type | | Bag | |
| Pitch - Termination Interface | | 0.50mm | Email productcompliance@molex.com |
| Temperature Range - Operating | | -40°C to +105°C | Please visit the <u>Contact Us</u> section for any |
| Wire Size AWG | | N/A | non-product compliance questions. |
| Wire/Cable Type | | Flat Flex Cable | China ROHS Not Reviewed |
| Electrical | | | ELV Not Reviewed |
| Current - Maximum | per Contact | 0.5A | |
| Voltage - Maximum | | 60V AC | |
| vollago maximum | | | |
| Material Info | | | Search Parts in this Series |
| Reference - Drawi | na Numbers | | |
| Packaging Specification | | PK-15166-001 | Use With |
| Sales Drawing | | SD-15166-001 | |

This document was generated on 07/11/2016

PK-15166-001 SD-15166-001

Use With

Molex FFC - FPC connector. Be sure to match like plating

This document was generated on 07/11/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION