

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151660456

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



K one company > a world of innovation

Sales Drawing

This document was generated on 07/11/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION		
Status:ActOverview:PremDescription:0.500	51660456 tive no-Flex™ Cable Jumpers mm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Type D) uits, 0.127m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating	,42
Documents: Drawing (PDF) Packaging Specification PK-	RoHS Certificate of Compliance (PDF)	
General		Series image - Reference only
Product Family Series Comments	Cable <u>15166</u> Contacts on opposite sides, Type D	EU ELV Not Reviewed
Crimp Quality Equipment Overview	Yes Premo-Flex™ Cable Jumpers	EU RoHS China RoHS
Product Name UPC	Premo-Flex™FFC Jumper 884982849549	Not Reviewed REACH SVHC
Physical		Not Reviewed <u>Halogen-Free</u>
Cable Length	0.127m	<u>Status</u>
Circuits (Loaded) Circuits (maximum) Net Weight	42 42 1.000/g	Not Reviewed Need more information on product environmental compliance?
Packaging Type Pitch - Termination Interface Temperature Range - Opera Wire Size AWG	· · · · · · · · · · · · · · · · · · ·	Email <u>productcompliance@molex.com</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions.
Wire/Cable Type	Flat Flex Cable	China ROHS Not Reviewed ELV Not Reviewed
Electrical Current - Maximum per Cont Voltage - Maximum	tact 0.5A 60V AC	
Material Info		Search Parts in this Series
Reference - Drawing Numb	pers	
Packaging Specification	PK-15166-001	Use With

PK-15166-001 SD-15166-001

Molex FFC - FPC connector. Be sure to match like plating

This document was generated on 07/11/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION