

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151660458

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Molex Connector Corporation: Excellent Integrated System Limited Datasheet of 0151660458 - FFC 0.50 TYPE D 42 CKTS LGT 152 Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

K one company > a world of innovation

Sales Drawing

| Part Number: | 0454660459 | | |
|---|---|---------------------------------------|---|
| Status: Active | | | |
| | | | |
| Overview: Premo-Flex™ Ca | | | |
| Description: | 0.50mm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Type D), 42 Circuits, 0.152m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating | | |
| | | | |
| Documents: | | | |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | |
| Packaging Specificat | tion PK-15166-001 (PD | <u>F)</u> | |
| General | | | Series image - Reference only |
| Product Family | | Cable | |
| Series | | <u>15166</u> | EU ELV |
| Comments | | Contacts on opposite sides, Type D | Not Reviewed |
| Crimp Quality Equipment | | Yes | |
| Overview | | Premo-Flex [™] Cable Jumpers | EU RoHS China RoHS |
| Product Name | | Premo-Flex™FFC Jumper | Not Reviewed |
| UPC | | 884982849563 | REACH SVHC |
| | | | Not Reviewed |
| Physical | | | Halogen-Free |
| Cable Length | | 0.152m | Status |
| Circuits (Loaded) | | 42 | Not Reviewed |
| Circuits (maximum) | | 42 | Need more information on product |
| Net Weight | | 1.000/g | environmental compliance? |
| Packaging Type Pitch - Termination Interface | | Bag 0.50mm | Email productcompliance@molex.com |
| Temperature Range - Operating | | 0.50mm -40°C to +105°C | Please visit the Contact Us section for any |
| Wire Size AWG | | -40°C to +105°C N/A | non-product compliance questions. |
| Wire/Cable Type | | Flat Flex Cable | |
| wire/Cable Type | | | China ROHS Not Reviewed |
| Electrical | | | ELV Not Reviewed |
| Current - Maximum p | per Contact | 0.5A | |
| Voltage - Maximum | | 60V AC | |
| Material Info | | | Search Parts in this Series |
| Deference Drawin | a Numbero | | <u>15166</u> Series |
| Reference - Drawing | | DK 15166 001 | |
| Packaging Specification | | PK-15166-001 | Use With |

This document was generated on 07/11/2016

PK-15166-001 SD-15166-001

Use With <a href="http://www.molex.com/product/

ffcfpc_th.html">Molex FFC - FPC connector. Be sure to match like plating

This document was generated on 07/11/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION