

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151670379

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



molex[®] one company > a world of innovation

	<u>51670379</u> stive		
	<u>mo-Flex™ Cable Jum</u>		
	ption: 1.00mm Pitch Premo-Flex [™] FFC Jumper, Same Side Contacts (Type A), 22 Circuits, 0.05m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating		
0.0	5m Cable Length, Cat	ble Thickness 0.12mm, Tin (Sn) Plating	
Documents:			
Drawing (PDF)		Packaging Specification PK-15167-001 (PDF)	N N
Product Specification PS-1	<u>5167-001 (PDF)</u>	RoHS Certificate of Compliance (PDF)	
General			Series image - Reference only
Product Family		Cable	
Series		<u>15167</u>	EU ELV
Comments		Contacts on the same side, Type A	Not Reviewed
Crimp Quality Equipment		Yes	EU RoHS China RoHS
Overview		Premo-Flex TM Cable Jumpers	Not Reviewed
Product Name		Premo-Flex™FFC Jumper	REACH SVHC
UPC		884982852624	Not Reviewed
Physical			Halogen-Free
Cable Length		0.051m	Status
Circuits (Loaded)		22	Not Reviewed
Circuits (maximum)		22	Need more information on product
Net Weight		1.000/g	environmental compliance?
Packaging Type		Bag	environmental compliance
Pitch - Termination Interface		1.00mm	Email productcompliance@molex.com
Temperature Range - Operating		-40°C to +105°C	Please visit the Contact Us section for any
Wire Size AWG		N/A	non-product compliance questions.
Wire/Cable Type		Flat Flex Cable	
51			China ROHS Not Reviewed
Electrical			ELV Not Reviewed
Current - Maximum per Cor	ntact	1.2A	
Voltage - Maximum		60V AC	
Material Info			Search Parts in this Series
Reference - Drawing Num	bers		
Packaging Specification		PK-15167-001	Use With
Product Specification		PS-15167-001	<a href="www.molex.com/link/ffc-</td></tr><tr><td rowspan=2 colspan=2>Sales Drawing</td><td>SD-15167-001</td><td>fpc.html">Molex FFC – FPC connector
	Be sure to match like plating		

This document was generated on 03/04/2016

This document was generated on 03/04/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION