

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151670589

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## molex<sup>®</sup> one company > a world of innovation

| Part Number: 01516<br>Status: Active | <u>70589</u>   |  |
|--------------------------------------|--|--|
| Overview: Premo-F                    | lex™ Cable Jumpers   |  |
|                                      | Pitch Premo-Flex™ FFC Jumper, Same Side Contacts (Type A), 40 Circ | uits,  |
|                                      | Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating             |  |
|                                      |  |  |
| Documents:                           |  |  |
| Drawing (PDF)                        | Packaging Specification PK-15167-001 (PDF)                         |  |
| Product Specification PS-15167       | 001 (PDF) RoHS Certificate of Compliance (PDF)                     |  |
| General                              |  | Series image - Reference only  |
| Product Family                       | Cable  |  |
| Series                               | <u>15167</u>   | EU ELV   |
| Comments                             | Contacts on the same side, Type A                                  | Not Reviewed   |
| Crimp Quality Equipment              | Yes  | FU DallS China DallS   |
| Overview                             | Premo-Flex <sup>™</sup> Cable Jumpers                              | EU RoHS China RoHS<br>Not Reviewed   |
| Product Name                         | Premo-Flex™FFC Jumper  | REACH SVHC   |
| UPC                                  | 884982854727   | Not Reviewed   |
| Physical                             |  | Halogen-Free   |
| Cable Length                         | 0.203m   | Status   |
| Circuits (Loaded)                    | 40   | Not Reviewed   |
| Circuits (maximum)                   | 40   | Need more information on product   |
| Net Weight                           | 1.000/g  | environmental compliance?  |
| Packaging Type                       | Bag  | environmental compliance :   |
| Pitch - Termination Interface        | 1.00mm   | Email productcompliance@molex.com  |
| Temperature Range - Operating        | -40°C to +105°C  | Please visit the Contact Us section for any  |
| Wire Size AWG                        | N/A  | non-product compliance questions.  |
| Wire/Cable Type                      | Flat Flex Cable  |  |
| 21                                   |  | China ROHS Not Reviewed  |
| Electrical                           |  | ELV Not Reviewed   |
| Current - Maximum per Contact        | 1.2A   |  |
| Voltage - Maximum                    | 60V AC   |  |
| Material Info                        |  | Search Parts in this Series  |
| Reference - Drawing Numbers          |  |  |
| Packaging Specification              | PK-15167-001   | Use With   |
| Product Specification                | PS-15167-001   | <a href="www.molex.com/link/ffc-&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Sales Drawing&lt;/td&gt;&lt;td&gt;SD-15167-001&lt;/td&gt;&lt;td&gt;fpc.html">Molex FFC – FPC connector</a> |
|                                      |  | Be sure to match like plating  |

This document was generated on 03/07/2016

## This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION