

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151680128

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



one company > a world of innovation

Part Number:	<u>0151680128</u>		
Status:	Active		
Overview:	Premo-Flex [™] Cable Jum	iners	
Description:		x TM FFC Jumper, Opposite Side Contacts (Type D), 8 Circuits,	
		able Thickness 0.12mm, Tin (Sn) Plating	
Documents:			
Drawing (PDF)		Packaging Specification PK-15168-001 (PDF)	
	on PS-15168-001 (PDF)	RoHS Certificate of Compliance (PDF)	
General			Series image - Reference only
Product Family		Cable	
Series		15168	EU ELV
Comments		Contacts on opposite sides, Type D	Not Reviewed
Crimp Quality Equipment		Yes	
Overview		Premo-Flex [™] Cable Jumpers	EU RoHS China RoHS
Product Name		Premo-Flex™FFC Jumper	Not Reviewed
UPC		884982855380	REACH SVHC
.			Not Reviewed
Physical		0.070	Halogen-Free
Cable Length		0.076m	Status
Circuits (Loaded)		8	Not Reviewed
Circuits (maximum)		-	Need more information on product
Net Weight		1.000/g	environmental compliance?
Packaging Type Pitch - Termination Interface		Bag 1.25mm	Email productcompliance@molex.com
Temperature Range - Operating		-40°C to +105°C	Please visit the Contact Us section for any
Wire Size AWG		N/A	non-product compliance questions.
Wire/Cable Type		Flat Flex Cable	
wite/Cable Type		That They Cable	China ROHS Not Reviewed
Electrical			ELV Not Reviewed
Current - Maximum	i per Contact	1.4A	
Voltage - Maximum	ı	60V AC	
Material Info			Search Parts in this Series
Reference - Drawi	ng Numbers		
Packaging Specification		PK-15168-001	Use With
Product Specificati		PS-15168-001	<pre><a href="www.molex.com/link/ffc-</pre></td></tr><tr><td>Sales Drawing</td><td></td><td>SD-15168-001</td><td>fpc.html">Molex FFC – FPC connector</pre>
5			Be sure to match like plating

This document was generated on 03/09/2016

This document was generated on 03/09/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION