

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151680207

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## molex<sup>®</sup> one company > a world of innovation

| PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION  |                  |   |   |
|---|------------------|---|---|
|   |                  | n <u>pers</u><br>xr™ FFC Jumper, Same Side Contacts (Type A), 14 Circuits,<br>able Thickness 0.12mm, Tin (Sn) Plating |   |
| Documents:<br>Drawing (PDF)<br>Product Specification PS | -15168-001 (PDF) | Packaging Specification PK-15168-001 (PDF)<br>RoHS Certificate of Compliance (PDF)                                    |   |
| General   |                  |   | Series image - Reference only   |
| Product Family<br>Series                                |                  | Cable<br>15168  | EUELV   |
| Comments  |                  | Contacts on the same side, Type A   | Not Reviewed  |
| Crimp Quality Equipment                                 |                  | Yes   | EU RoHS China RoHS  |
| Overview<br>Product Name                                |                  | <u>Premo-Flex™ Cable Jumpers</u><br>Premo-Flex™FFC Jumper   | Not Reviewed  |
| UPC   |                  | 884982856172  | REACH SVHC  |
| UPC   |                  | 004902030172  | Not Reviewed  |
| Physical  |                  |   | Halogen-Free  |
| Cable Length  |                  | 0.254m  | Status  |
| Circuits (Loaded)                                       |                  | 14  | Not Reviewed  |
| Circuits (maximum)                                      |                  | 14  | Need more information on product  |
| Net Weight  |                  | 1.000/g   | environmental compliance?   |
| Packaging Type  |                  | Bag   | entri ennientai eempiianee.   |
| Pitch - Termination Interface                           |                  | 1.25mm  | Email productcompliance@molex.com   |
| Temperature Range - Operating                           |                  | -40°C to +105°C   | Please visit the <u>Contact Us</u> section for any  |
| Wire Size AWG   |                  | N/A   | non-product compliance questions.   |
| Wire/Cable Type   |                  | Flat Flex Cable   | China ROHS Not Reviewed   |
| Electrical  |                  |   | ELV Not Reviewed  |
| Current - Maximum per C                                 | Contact          | 1.4A  |   |
| Voltage - Maximum                                       |                  | 60V AC  |   |
| Material Info   |                  |   | Search Parts in this Series<br>15168 Series   |
| Reference - Drawing Nu                                  | Imbers           |   |   |
| Packaging Specification                                 |                  | PK-15168-001  | Use With  |
| Product Specification                                   |                  | PS-15168-001  | <a href="www.molex.com/link/ffc-&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Sales Drawing&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;td&gt;SD-15168-001&lt;/td&gt;&lt;td&gt;fpc.html">Molex FFC – FPC connector</a> |

This document was generated on 03/02/2016

This document was generated on 03/02/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Be sure to match like plating