

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Molex Connector Corporation 0151680227

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



molex[®] one company > a world of innovation

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION			
Part Number: 0151680227 Status: Active Overview: Premo-Flex™ Cable Ju Description: 1.25mm Pitch Premo-F 0.229m Cable Length, 0		<u>npers</u> ıx™ FFC Jumper, Same Side Contacts (Type A), 16 Circuits, able Thickness 0.12mm, Tin (Sn) Plating	
Documents: Drawing (PDF) Product Specification F	2S-15168-001 (PDF)	Packaging Specification PK-15168-001 (PDF) RoHS Certificate of Compliance (PDF)	
General			Series image - Reference only
Product Family Series Comments		Cable <u>15168</u> Contacts on the same side, Type A	EU ELV Not Reviewed
Crimp Quality Equipme Overview Product Name UPC	ent	Yes <u>Premo-Flex™ Cable Jumpers</u> Premo-Flex™FFC Jumper 884982856370	EU RoHS China RoHS Not Reviewed REACH SVHC Not Reviewed
Physical Cable Length Circuits (Loaded)		0.229m 16	Halogen-Free Status Not Reviewed
Circuits (maximum) Net Weight Packaging Type		16 1.000/g Bag	Need more information on product environmental compliance?
Pitch - Termination Interface Temperature Range - Operating Wire Size AWG		1.25mm -40°C to +105°C N/A	Email productcompliance@molex.com Please visit the <u>Contact Us</u> section for any non-product compliance questions.
Wire/Cable Type Electrical		Flat Flex Cable	China ROHS Not Reviewed ELV Not Reviewed
Current - Maximum per Voltage - Maximum	r Contact	1.4A 60V AC	
Material Info Reference - Drawing Numbers		Search Parts in this Series 15168 Series	
Packaging Specification Product Specification Sales Drawing		PK-15168-001 PS-15168-001 SD-15168-001	Use With <a href="www.molex.com/link/ffc-
fpc.html">Molex FFC – FPC connector

This document was generated on 03/07/2016

This document was generated on 03/07/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Be sure to match like plating